

# Safety Data Sheet according to (EC) No 1907/2006

Page 1 of 8

sds no.: 153536 V002.1

Revision: 18.03.2011 printing date: 04.05.2011

printing date: 04.03.2011

Loctite 422

# 1. Identification of the substance/mixture and of the company/undertaking

#### **Product identifier:**

Loctite 422

### Relevant identified uses of the substance or mixture and uses advised against:

Intended use: Cyanoacrylate

## Details of the supplier of the safety data sheet:

Henkel Ireland Limited Product Safety & Regulatory Affairs Tallaght Business Park, Whitestown Dublin 24

Ireland

Phone: +353 (14046444) Fax-no.: +353 (14519926)

ua-productsafety.uk@uk.henkel.com

## **Emergency telephone number:**

24 Hours Emergency Tel: +44 (0)1442 278497

## 2. Hazards identification

## Classification of the substance or mixture:

### Classification (DPD):

Xi - Irritant

R36/37/38 Irritating to eyes, respiratory system and skin.

MSDS-No.: 153536 Loctite 422 Page 2 of 8

V002.1

### Label elements (DPD):

#### Xi - Irritant



#### Risk phrases:

R36/37/38 Irritating to eyes, respiratory system and skin.

#### Safety phrases:

S23 Do not breathe vapour.

S24/25 Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

#### Additional labeling:

Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children.

#### Other hazards:

Sticks skin and eyelids together in seconds.

Pregnant women should absolutely avoid breathe in and skin contact.

### 3. Composition/information on ingredients

### General chemical description:

Cyanoacrylate Adhesive

### Declaration of the ingredients according to CLP (EC) No 1272/2008:

| Hazardous components  | EC Number        | content       | Classification                          |
|-----------------------|------------------|---------------|---|
| CAS-No.               | REACH-Reg No.    |               |   |
| Ethyl 2-cyanoacrylate | 230-391-5        | > 80- < 100 % | Skin irritation 2                       |
| 7085-85-0             | 01-2119527766-29 |               | H315                                    |
|                       |                  |               | Specific target organ toxicity - single |
|                       |                  |               | exposure 3                              |
|                       |                  |               | H335                                    |
|                       |                  |               | Serious eye irritation 2                |
|                       |                  |               | H319                                    |

Only dangerous ingredients for which a CLP classification is already available are displayed in this table. For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

#### Declaration of ingredients according to DPD (EC) No 1999/45:

| Hazardous components               | EC Number                     | content        | Classification           |
|------------------------------------|-------------------------------|----------------|--------------------------|
| CAS-No.                            | REACH-Reg No.                 |                |                          |
| Ethyl 2-cyanoacrylate<br>7085-85-0 | 230-391-5<br>01-2119527766-29 | > 80 - < 100 % | Xi - Irritant; R36/37/38 |

For full text of the R-Phrases indicated by codes see section 16 'Other Information'. Substances without classification may have community workplace exposure limits available.

### 4. First aid measures

### Description of first aid measures:

MSDS-No.: 153536 Loctite 422 Page 3 of 8

V002.1

#### Inhalation:

Move to fresh air, consult doctor if complaint persists.

#### Skin contact:

Do not pull bonded skin apart. It may be gently peeled apart using a blunt object such as a spoon, preferably after soaking in warm soapy water.

Cyanoacrylates give off heat on solidification. In rare cases a large drop will generate enough heat to cause a burn.

Burns should be treated normally after the adhesive has been removed from the skin.

If lips are accidentally stuck together apply warm water to the lips and encourage maximum wetting and pressure from saliva inside the mouth

Peel or roll lips apart. Do not try to pull the lips apart with direct opposing action.

#### Eye contact:

If the eye is bonded closed, release eyelashes with warm water by covering with wet pad.

Cyanoacrylate will bond to eye protein and will cause periods of weeping which will help to debond the adhesive.

Keep eye covered until debonding is complete, usually within 1-3 days.

Do not force eye open. Medical advice should be sought in case solid particles of cyanoacrylate trapped behind the eyelid cause any abrasive damage.

#### Ingestion:

Ensure that breathing passages are not obstructed. The product will polymerise immediately in the mouth making it almost impossible to swallow. Saliva will slowly separate the solidified product from the mouth (several hours).

#### Most important symptoms and effects, both acute and delayed:

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

EYE: Irritation, conjunctivitis.

SKIN: Redness, inflammation.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

#### Indication of any immediate medical attention and special treatment needed:

See section: Description of first aid measures

### 5. Firefighting measures

#### **Extinguishing media:**

#### Suitable extinguishing media:

Foam, extinguishing powder, carbon dioxide.

Fine water spray

#### Special hazards arising from the substance or mixture:

Oxides of carbon, oxides of nitrogen, irritating organic vapors.

#### Advice for firefighters:

Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA).

#### 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation.

## **Environmental precautions:**

Do not let product enter drains.

#### Methods and material for containment and cleaning up:

Do not use cloths for mopping up. Flood with water to complete polymerization and scrape off the floor. Cured material can be disposed of as non-hazardous waste.

#### Reference to other sections:

See advice in chapter 8

MSDS-No.: 153536 Loctite 422 Page 4 of 8

V002.1

# 7. Handling and storage

#### Precautions for safe handling:

Ventilation (low level) is recommended when using large volumes

Use of dispensing equipment is recommended to minimise the risk of skin or eye contact

#### Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Good industrial hygiene practices should be observed.

#### Conditions for safe storage, including any incompatibilities:

For optimum shelf life store in original containers under refrigerated conditions at 2 - 8°C (35.6 - 46.4 °F)

#### **Specific end use(s):**

Cyanoacrylate

## 8. Exposure controls/personal protection

#### **Control parameters:**

Valid for

Great Britain

| Ingredient          | ppm | mg/m <sup>3</sup> | Type                | Category | Remarks  |
|---------------------|-----|-------------------|---------------------|----------|----------|
| ETHYL CYANOACRYLATE | 0,3 | 1,5               | Short Term Exposure |          | EH40 WEL |
| 7085-85-0           |     |                   | Limit (STEL):       |          |          |

#### **Exposure controls:**

Respiratory protection:

Ensure adequate ventilation.

#### Hand protection:

The use of chemical resistant gloves such as Nitrile are recommended.

Polyethylene or polypropylene gloves are recommended when using large volumes.

Do not use PVC, rubber or nylon gloves.

Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed then the gloves should be replaced.

### Eye protection:

Wear protective glasses.

## 9. Physical and chemical properties

pH No data available / Not applicable

Initial boiling point > 149 °C (> 300.2 °F)

Flash point 80 - 93,4 °C (176 - 200.12 °F); Tagliabue closed cup

Decomposition temperature No data available / Not applicable

Vapour pressure 0,6 mbar Density 1,1 g/cm3

(20 °C (68 °F))

Bulk density

No data available / Not applicable

Viscosity

No data available / Not applicable

Viscosity (kinematic)

No data available / Not applicable

Explosive properties

No data available / Not applicable

Solubility (qualitative) Miscible

(Solvent: Acetone)

Solidification temperature No data available / Not applicable Melting point No data available / Not applicable

MSDS-No.: 153536 Loctite 422 Page 5 of 8

V002.1

Flammability
Auto-ignition temperature
No data available / Not applicable
Explosive limits
No data available / Not applicable
Partition coefficient: n-octanol/water
No data available / Not applicable
Evaporation rate
No data available / Not applicable
Vapor density
No data available / Not applicable
Oxidising properties
No data available / Not applicable
No data available / Not applicable

#### Other information:

No data available / Not applicable

### 10. Stability and reactivity

#### Reactivity:

Rapid exothermic polymerization will occur in the presence of water, amines, alkalis and alcohols.

#### **Chemical stability:**

Stable under recommended storage conditions.

#### Possibility of hazardous reactions:

See section reactivity

#### Conditions to avoid:

Stable under normal conditions of storage and use.

#### **Incompatible materials:**

None if used properly.

## 11. Toxicological information

#### General toxicological information:

The preparation is classified based on the conventional method outlined in Article 6(1)(a) of Directive 1999/45/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

## Oral toxicity:

Cyanoacrylates are considered to have relatively low toxicity. Acute oral LD50 is >5000mg/kg (rat). It is almost impossible to swallow as it rapidly polymerises in the mouth.

## Inhalative toxicity:

Irritating to respiratory system

Prolonged exposure to high concentrations of vapours may lead to chronic effects in sensitive individuals

In dry atmosphere with < 50% humidity, vapours may irritate the eyes and respiratory system

#### Skin irritation:

Irritating to the skin.

Bonds skin in seconds. Considered to be of low toxicity: acute dermal LD50 (rabbit)>2000mg/kg

Due to polymerisation at the skin surface allergic reaction is unlikely to occur

#### Eye irritation:

Irritating to eyes.

Liquid product will bond eyelids. In a dry atmosphere (RH<50%) vapours may cause irritation and lachrymatory effect

## Acute toxicity:

| Hazardous components               | Value        | Value                          | Route of       | Exposure | Species       | Method   |
|------------------------------------|--------------|--------------------------------|----------------|----------|---------------|--|
| CAS-No.                            | type         |                                | application    | time     |               |  |
| Ethyl 2-cyanoacrylate<br>7085-85-0 | LD50<br>LD50 | > 5.000 mg/kg<br>> 2.000 mg/kg | oral<br>dermal |          | rat<br>rabbit | OECD Guideline 401 (Acute<br>Oral Toxicity)<br>OECD Guideline 402 (Acute<br>Dermal Toxicity) |

MSDS-No.: 153536 Loctite 422 Page 6 of 8

V002.1

### Skin corrosion/irritation:

| Hazardous components CAS-No.    | Result              | Exposure<br>time | Species | Method  |
|---------------------------------|---------------------|------------------|---------|---|
| Ethyl 2-cyanoacrylate 7085-85-0 | slightly irritating | 24 h             | rabbit  | OECD Guideline 404 (Acute<br>Dermal Irritation / Corrosion) |

## Serious eye damage/irritation:

| Hazardous components CAS-No. | Result         | Exposure<br>time | Species | Method                      |
|------------------------------|----------------|------------------|---------|-----------------------------|
| Ethyl 2-cyanoacrylate        | not irritating | 72 h             | rabbit  | OECD Guideline 405 (Acute   |
| 7085-85-0                    |                |                  |         | Eye Irritation / Corrosion) |

## Germ cell mutagenicity:

| Hazardous components CAS-No.    | Result                           | Type of study /<br>Route of<br>administration  | Metabolic<br>activation /<br>Exposure time | Species | Method   |
|---------------------------------|----------------------------------|--|--|---------|--|
| Ethyl 2-cyanoacrylate 7085-85-0 | negative<br>negative<br>negative | bacterial reverse<br>mutation assay (e.g<br>Ames test)<br>in vitro mammalian<br>chromosome<br>aberration test<br>mammalian cell<br>gene mutation assay | with and without<br>with and without       |         | OECD Guideline 471 (Bacterial Reverse Mutation Assay) OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |

# 12. Ecological information

#### General ecological information:

Biological and Chemical Oxygen Demands (BOD and COD) are insignificant.

Do not empty into drains / surface water / ground water.

The preparation is classified based on the conventional method outlined in Article 6(1)(a) of Directive 1999/45/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

## Mobility:

Cured adhesives are immobile.

### Persistence and degradability:

| Hazardous components<br>CAS-No. | Result | Route of application | Degradability | Method                          |
|---------------------------------|--------|----------------------|---------------|---------------------------------|
| Ethyl 2-cyanoacrylate           |        | aerobic              | 57 %          | OECD Guideline 301 D (Ready     |
| 7085-85-0                       |        |                      |               | Biodegradability: Closed Bottle |
|                                 |        |                      |               | Test)                           |

## Bioaccumulative potential / Mobility in soil:

| Hazardous components CAS-No. | LogKow | Bioconcentration<br>factor (BCF) | Exposure time | Species | Temperature | Method                   |
|------------------------------|--------|----------------------------------|---------------|---------|-------------|--------------------------|
| Ethyl 2-cyanoacrylate        | 0,776  |                                  |               |         | 22 °C       | EU Method A.8 (Partition |
| 7085-85-0                    |        |                                  |               |         |             | Coefficient)             |

# 13. Disposal considerations

# Waste treatment methods:

MSDS-No.: 153536 Loctite 422 Page 7 of 8

V002.1

### Product disposal:

Cured adhesive: Dispose of as water insoluble non-toxic solid chemical in authorised landfill or incinerate under controlled conditions.

Dispose of in accordance with local and national regulations.

Contribution of this product to waste is very insignificant in comparison to article in which it is used

#### Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

#### Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

# 14. Transport information

#### Road transport ADR:

Not dangerous goods

#### Railroad transport RID:

Not dangerous goods

#### Inland water transport ADN:

Not dangerous goods

## Marine transport IMDG:

Not dangerous goods

#### Air transport IATA:

Class: 9

Packaging group:

Packaging instructions (passenger) Packaging instructions (cargo)

UN no.: 3334 Label: 9

Proper shipping name: Aviation regulated liquid, n.o.s. (Cyanoacrylate ester)

Primary packs containing less than 500ml are unregulated by this mode of transport and may be shipped unrestricted.

## 15. Regulatory information

### Safety, health and environmental regulations/legislation specific for the substance or mixture:

VOC content < 3,00 % (1999/13/EC)

MSDS-No.: 153536 Loctite 422 Page 8 of 8

V002.1

## 16. Other information

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

R36/37/38 Irritating to eyes, respiratory system and skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

#### **Further information:**

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

particular properties.

This safety data sheet was prepared in accordance with Council Directive 67/548/EEC and it's subsequent amendments, and Commission Directive 1999/45/EC.