

Loctite 511

Safety Data Sheet according to (EC) No 1907/2006 - ISO 11014-1

Page 1 of 6

sds no.: 173048

V004.0

Revision: 20.05.2010 printing date: 08.06.2011

1. Identification of the substance/preparation and of the company/undertaking

Trade name:

Loctite 511

Intended use:

Anaerobic

Company name:

Henkel Ireland Limited Product Safety & Regulatory Affairs Tallaght Business Park, Whitestown Dublin 24

Ireland

Phone: +353 (14046444) Fax-no.: +353 (14519926)

E-mail address of person responsible for Safety Data Sheet:

ua-productsafety.uk@uk.henkel.com

Emergency information:

24 Hours Emergency Tel: +44 (0)1442 278497

2. Hazards identification

R36/37/38 Irritating to eyes, respiratory system and skin.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R43 May cause sensitisation by skin contact.

3. Composition / information on ingredients

General chemical description:

Anaerobic Sealant

Declaration of ingredients according to (EC) No 1907/2006:

MSDS-No.: 173048 Loctite 511 Page 2 of 6

V004.0

Hazardous components CAS-No.	EINECS ELINCS	content	Classification
2-Ethylhexyl methacrylate 688-84-6	211-708-6	5 - 10 %	Xi - Irritant; R36/37/38
Decan-1-ol 112-30-1	203-956-9	5 - 10 %	Xi - Irritant; R36/38 N - Dangerous for the environment; R51/53
Cumene hydroperoxide 80-15-9	201-254-7	1 -< 3 %	T - Toxic; R23 Xn - Harmful; R21/22, R48/20/22 O - Oxidizing; R7 C - Corrosive; R34 N - Dangerous for the environment; R51, R53
Cumene 98-82-8	202-704-5	0,1 - 1 %	R10 Xn - Harmful; R65 Xi - Irritant; R37 N - Dangerous for the environment; R51, R53
Maleic acid 110-16-7	203-742-5	0,1 - 1 %	Xn - Harmful; R22 Xi - Irritant; R36/37/38 R43

For full text of the R-Phrases indicated by codes see section 16 'Other Information'.

Substances without classification may have community workplace exposure limits available.

4. First aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Seek medical advice.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

Ingestion:

Rinse out mouth, drink 1-2 glasses of water, do not induce vomiting.

Seek medical advice.

5. Fire fighting measures

Suitable extinguishing media:

Carbon dioxide, foam, powder

Special protection equipment for firefighters:

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Hazardous combustion products:

Oxides of carbon, oxides of nitrogen, irritating organic vapors.

6. Accidental release measures

Personal precautions:

Avoid skin and eye contact.

Ensure adequate ventilation.

Environmental precautions:

Do not let product enter drains.

Clean-up methods:

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

For small spills wipe up with paper towel and place in container for disposal.

MSDS-No.: 173048 Loctite 511 Page 3 of 6

V004.0

7. Handling and storage

Handling:

Use only in well-ventilated areas.

Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.

Storage

Store in original containers at 8-21C (46.4-69.8F) and do not return residual materials to containers as contamination may reduce the shelf life of the bulk product.

8. Exposure controls / personal protection

Components with specific control parameters for workplace:

Valid for

Great Britain

Basis

UK EH40 WELs

Ingredient	ppm	mg/m3	Type	Category	Remarks
CUMENE	25	125	Time Weighted Average		EH40 WEL
98-82-8			(TWA).		
CUMENE	50	250	Short Term Exposure		EH40 WEL
98-82-8			Limit (STEL):		
CUMENE			Skin designation:	Can be absorbed through the	EH40 WEL
98-82-8				skin.	
CUMENE			Skin designation:	Can be absorbed through the	ECTLV
98-82-8				skin.	
CUMENE	50	250	Short Term Exposure	Indicative	ECTLV
98-82-8			Limit (STEL):		
CUMENE	20	100	Time Weighted Average	Indicative	ECTLV
98-82-8			(TWA).		

Respiratory protection:

Use only in well-ventilated areas.

Hand protection:

The use of chemical resistant gloves such as Nitrile are recommended.

Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed then the gloves should be replaced.

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (IIR; \geq = 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (IIR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Wear protective glasses.

Skin protection:

Wear suitable protective clothing.

General protection and hygiene measures:

Good industrial hygiene practices should be observed.

MSDS-No.: 173048 Loctite 511 Page 4 of 6

V004.0

9. Physical and chemical properties

General characteristics:

Appearance Paste White Odor: alcohol-like

Phys./chem. properties:

pH-value not applicable Boiling point Not determined Flash point $> 100 \, ^{\circ}\mathrm{C} \, (> 212 \, ^{\circ}\mathrm{F})$ Vapor pressure $< 3 \, \mathrm{mm} \, \mathrm{hg}$

(20 °C (68 °F))

Density 1,05 g/cm3

Solubility (qualitative) Not miscible (Solvent: Water)

Vapor density: Not available

VOC content <5 % (As defined in the Council Directive 2004/42/EC)

(2004/42/EC)

10. Stability and reactivity

Conditions to avoid:

Stable

Materials to avoid:

Reaction with strong acids. Reacts with strong oxidants.

Hazardous decomposition products:

Irritating organic vapours. Oxides of carbon. Sulphur oxides nitrogen oxides

11. Toxicological information

Oral toxicity:

This material is considered to have low toxicity if swallowed.

Inhalative toxicity:

Irritating to respiratory system

Skin irritation:

Irritating to the skin.

Eye irritation:

Irritating to eyes.

Sensitizing:

May cause sensitization by skin contact.

12. Ecological information

Ecotoxicity:

Harmful to aquatic organisms.

May cause long-term adverse effects in the aquatic environment.

Do not empty into drains \slash surface water \slash ground water.

Mobility:

Cured adhesives are immobile.

MSDS-No.: 173048 Loctite 511 Page 5 of 6

V004.0

Persistence and Biodegradability:

No data available.

Bioaccumulative potential:

No data available.

Ecotoxicity:

Hazardous components	Species	Exposure	Value	Value
CAS-No.		time	type	
Decan-1-ol 112-30-1	Fathead minnow (Pimephales promelas)	96 h	LC 50	2,2 - 2,5 mg/l
Cumene hydroperoxide 80-15-9 Cumene hydroperoxide	Ide, silver or golden orfe (Leuciscus idus) Water flea (Daphnia magna)	48 h 24 h	LC 50 EC 50	14 mg/l 7 mg/l
80-15-9				
Cumene 98-82-8	Trout family (Salmonidae)	96 h	LC 50	4,8 mg/l

General ecological information:

Cured Loctite products are typical polymers and do not pose any immediate environmental hazards.

13. Disposal considerations

Product disposal:

Dispose of in accordance with local and national regulations.

Contribution of this product to waste is very insignificant in comparison to article in which it is used

Waste code():

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

14. Transport information

General information:

Not hazardous according to RID, ADR, ADNR, IMDG, IATA-DGR.

15. Regulations - classification and identification

Indication of danger:

Xi - Irritant



Contains

Maleic acid

Risk phrases:

R36/37/38 Irritating to eyes, respiratory system and skin.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R43 May cause sensitisation by skin contact.

MSDS-No.: 173048 Loctite 511 Page 6 of 6

V004.0

Safety phrases:

S23 Do not breathe vapour.

S24/25 Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S37 Wear suitable gloves.

S51 Use only in well-ventilated areas.

S61 Avoid release to the environment. Refer to special instructions/Safety data sheets.

Additional labeling:

For consumer use only: S2 Keep out of the reach of children

S46 If swallowed, seek medical advice immediately and show this container or label.

16. Other information

The labelling of the product is indicated in Section 15. The full text of the R-phrases indicted by codes in this safety data sheet are as follows:

R10 Flammable.

R21/22 Harmful in contact with skin and if swallowed.

R22 Harmful if swallowed.

R23 Toxic by inhalation.

R34 Causes burns.

R36/37/38 Irritating to eyes, respiratory system and skin.

R36/38 Irritating to eyes and skin.

R37 Irritating to respiratory system.

R43 May cause sensitisation by skin contact.

R48/20/22 Harmful: danger of serious damage to health by prolonged exposure through inhalation and if swallowed.

R51 Toxic to aquatic organisms.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R53 May cause long-term adverse effects in the aquatic environment.

R65 Harmful: may cause lung damage if swallowed.

R7 May cause fire.

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

This safety data sheet was prepared in accordance with Council Directive 67/548/EEC and it's subsequent amendments, and Commission Directive 1999/45/EC.