

Safety Data Sheet according to (EC) No 1907/2006

Page 1 of 9

sds no.: 153640 V003.1

Revision: 03.06.2011

printing date: 08.06.2011

Loctite 561

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier:

Loctite 561

Relevant identified uses of the substance or mixture and uses advised against:

Intended use:

Sealant

Details of the supplier of the safety data sheet:

Henkel Ireland Limited Product Safety & Regulatory Affairs Tallaght Business Park, Whitestown Dublin 24

Ireland

Phone: +353 (14046444) +353 (14519926) Fax-no.:

ua-productsafety.uk@uk.henkel.com

Emergency telephone number:

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

Classification of the substance or mixture:

Classification (DPD):

No classification required.

Label elements (DPD):

Risk phrases:

Not classified as hazardous.

Other hazards:

None if used properly.

SECTION 3: Composition/information on ingredients

General chemical description:

Anaerobic Sealant

MSDS-No.: 153640 Loctite 561 Page 2 of 9

V003.1

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components	EC Number	content	Classification
CAS-No.	REACH-Reg No.		
Cumene hydroperoxide	201-254-7	> 0,1-< 1 %	Acute toxicity 4; Dermal
80-15-9			H312
			Specific target organ toxicity - repeated
			exposure 2
			H373
			Acute toxicity 3; Inhalation
			H331
			Acute toxicity 4; Oral
			H302
			Organic peroxides E
			H242
			Chronic hazards to the aquatic environment 2
			H411
			Skin corrosion 1B
			H314
Cumene	202-704-5	> 0,1-< 0,5 %	Flammable liquids 3
98-82-8			H226
			Aspiration hazard 1
			H304
			Specific target organ toxicity - single
			exposure 3
			H335
			Chronic hazards to the aquatic environment 2
			H411
Ethane-1,2-diol	203-473-3	> 1-< 5 %	Acute toxicity 4; Oral
107-21-1			H302

Only dangerous ingredients for which a CLP classification is already available are displayed in this table. For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

Declaration of ingredients according to DPD (EC) No 1999/45:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Cumene hydroperoxide	201-254-7	> 0,1 -< 1 %	T - Toxic; R23
80-15-9			Xn - Harmful; R21/22, R48/20/22
			O - Oxidizing; R7
			C - Corrosive; R34
			N - Dangerous for the environment; R51, R53
Cumene	202-704-5	> 0,1 - < 0,5 %	R10
98-82-8			Xn - Harmful; R65
			Xi - Irritant; R37
			N - Dangerous for the environment; R51, R53
Ethane-1,2-diol	203-473-3	> 1 - < 5 %	Xn - Harmful; R22
107-21-1			

For full text of the R-Phrases indicated by codes see section 16 'Other Information'. Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

Description of first aid measures:

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Seek medical advice.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

MSDS-No.: 153640 Loctite 561 Page 3 of 9

V003.1

Ingestion:

Rinse out mouth, drink 1-2 glasses of water, do not induce vomiting.

Seek medical advice.

Most important symptoms and effects, both acute and delayed:

SKIN: Rash, Urticaria.

Indication of any immediate medical attention and special treatment needed:

See section: Description of first aid measures

SECTION 5: Firefighting measures

Extinguishing media:

Suitable extinguishing media:

Carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

None known

Special hazards arising from the substance or mixture:

None

Oxides of carbon.

Advice for firefighters:

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Avoid skin and eye contact.

Environmental precautions:

Do not let product enter drains.

Methods and material for containment and cleaning up:

For small spills wipe up with paper towel and place in container for disposal.

Reference to other sections:

See advice in chapter 8

SECTION 7: Handling and storage

Precautions for safe handling:

Use only in well-ventilated areas.

Avoid skin and eye contact.

Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.

Hygiene measures:

Good industrial hygiene practices should be observed.

Conditions for safe storage, including any incompatibilities:

Store in original containers at 8-21°C (46.4-69.8°F) and do not return residual materials to containers as contamination may reduce the shelf life of the bulk product.

Specific end use(s):

Sealant

MSDS-No.: 153640 Loctite 561 Page 4 of 9

V003.1

SECTION 8: Exposure controls/personal protection

Control parameters:

Valid for

Great Britain

Basis

UK EH40 WELs

Ingredient	ppm	mg/m3	Type	Category	Remarks
CUMENE	25	125	Time Weighted Average		EH40 WEL
98-82-8			(TWA):		
CUMENE	50	250	Short Term Exposure		EH40 WEL
98-82-8			Limit (STEL):		
CUMENE			Skin designation:	Can be absorbed through the	EH40 WEL
98-82-8				skin.	
CUMENE			Skin designation:	Can be absorbed through the	ECTLV
98-82-8				skin.	
CUMENE	50	250	Short Term Exposure	Indicative	ECTLV
98-82-8			Limit (STEL):		
CUMENE	20	100	Time Weighted Average	Indicative	ECTLV
98-82-8			(TWA):		
ETHYLENE GLYCOL			Skin designation:	Can be absorbed through the	ECTLV
107-21-1				skin.	
ETHANE-1,2-DIOL, VAPOUR	40	104	Short Term Exposure		EH40 WEL
107-21-1			Limit (STEL):		
ETHANE-1,2-DIOL, PARTICULATE			Skin designation:	Can be absorbed through the	EH40 WEL
107-21-1				skin.	
ETHANE-1,2-DIOL, VAPOUR			Skin designation:	Can be absorbed through the	EH40 WEL
107-21-1				skin.	
ETHANE-1,2-DIOL, PARTICULATE		10	Time Weighted Average		EH40 WEL
107-21-1			(TWA):		
ETHANE-1,2-DIOL, VAPOUR	20	52	Time Weighted Average		EH40 WEL
107-21-1			(TWA):		
ETHYLENE GLYCOL	20	52	Time Weighted Average	Indicative	ECTLV
107-21-1			(TWA):		
ETHYLENE GLYCOL	40	104	Short Term Exposure	Indicative	ECTLV
107-21-1			Limit (STEL):		

Exposure controls:

Respiratory protection:

Use only in well-ventilated areas.

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Wear protective glasses.

Skin protection:

Wear suitable protective clothing.

MSDS-No.: 153640 Loctite 561 Page 5 of 9

V003.1

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties:

Appearance waxy
Off white
Odor Mild

pH No data available / Not applicable

Initial boiling point > 150 °C (> 302 °F) Flash point Not applicable

Decomposition temperature No data available / Not applicable

Vapour pressure < 13 mbar

(25 °C (77 °F))

Density 1,14 g/cm3

()
Bulk density
No data available / Not applicable
Viscosity
No data available / Not applicable
Viscosity (kinematic)
No data available / Not applicable
Explosive properties
No data available / Not applicable

Solubility (qualitative) Slight

(Solvent: Water)

Solidification temperature No data available / Not applicable Melting point No data available / Not applicable Flammability No data available / Not applicable Auto-ignition temperature No data available / Not applicable No data available / Not applicable Explosive limits No data available / Not applicable Partition coefficient: n-octanol/water No data available / Not applicable Evaporation rate Vapor density No data available / Not applicable Oxidising properties No data available / Not applicable

Other information:

No data available / Not applicable

SECTION 10: Stability and reactivity

Reactivity:

Reaction with strong acids. Reacts with strong oxidants.

Chemical stability:

Stable under recommended storage conditions.

Possibility of hazardous reactions:

See section reactivity

Conditions to avoid:

Stable

Incompatible materials:

No data available.

Hazardous decomposition products:

Oxides of carbon.

SECTION 11: Toxicological information

General toxicological information:

The preparation is classified based on the conventional method outlined in Article 6(1)(a) of Directive 1999/45/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

Oral toxicity:

This material is considered to have low toxicity if swallowed.

MSDS-No.: 153640 Loctite 561 Page 6 of 9

V003.1

Inhalative toxicity:

May cause irritation to respiratory system.

Skin irritation:

Prolonged or repeated contact may cause skin irritation.

Eye irritation:

Avoid eye contact.

Acute toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		
Cumene hydroperoxide	LD50	550 mg/kg	oral		rat	
80-15-9	LC50	220 ppm	inhalation	4 h	rat	
Į.	LD50	500 mg/kg	dermal		rat	
Ethane-1,2-diol	LD50	> 2.000 mg/kg	oral		rat	EU Method B.1 (Acute
107-21-1						Toxicity (Oral))

Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Cumene hydroperoxide	corrosive		rabbit	
80-15-9				

Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Cumene hydroperoxide 80-15-9	positive	bacterial reverse mutation assay (e.g Ames test)	without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Cumene hydroperoxide 80-15-9	negative	dermal		mouse	
Ethane-1,2-diol 107-21-1	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

The preparation is classified based on the conventional method outlined in Article 6(1)(a) of Directive 1999/45/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

Mobility:

Cured adhesives are immobile.

MSDS-No.: 153640 Loctite 561 Page 7 of 9

V003.1

Toxicity:

Hazardous components CAS-No.	Value type	Value	Acute Toxicity	Exposure time	Species	Method
	• •		Study			
Cumene hydroperoxide	LC50	3,9 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline
80-15-9		•				203 (Fish, Acute
						Toxicity Test)
Cumene hydroperoxide	EC50	18 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline
80-15-9						202 (Daphnia sp.
						Acute
						Immobilisation
						Test)
Cumene hydroperoxide	ErC50	3,1 mg/l	Algae	72 h	Pseudokirchnerella subcapitata	OECD Guideline
80-15-9						201 (Alga, Growth
						Inhibition Test)
Cumene	LC50	4,8 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline
98-82-8						203 (Fish, Acute
						Toxicity Test)
Cumene	EC50	4 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline
98-82-8						202 (Daphnia sp.
						Acute
						Immobilisation
	FG50	2.5 "		50. 1	a .	Test)
Cumene	EC50	2,6 mg/l	Algae	72 h	Selenastrum capricornutum	OECD Guideline
98-82-8					(new name: Pseudokirchnerella	. (0)
Ednama 1.2 dial	NOEC	15 200 //	Fish	28 d	subcapitata)	Inhibition Test) OECD Guideline
Ethane-1,2-diol 107-21-1	NOEC	15.380 mg/l	FISH	28 d	Oryzias latipes	204 (Fish,
107-21-1						Prolonged Toxicity
						Test: 14-day Study)
	LC50	72.860 mg/l	Fish	96 h	Pimephales promelas	OECD Guideline
	LC30	72.000 mg/1	1 1511)0 II	i inicpliales profficias	203 (Fish, Acute
						Toxicity Test)
Ethane-1,2-diol	EC50	34.400 mg/l	Daphnia	48 h	Ceriodaphnia sp.	OECD Guideline
107-21-1	Leso	51.100 mg1	Барина	10 11	Cerrodapinia sp.	202 (Daphnia sp.
107-21-1						Acute
						Immobilisation
						Test)
Ethane-1,2-diol	EC50	> 20.000 mg/l	Algae	1	Microcystis aeruginosa	OECD Guideline
107-21-1	2000	. 20.000 mg 1	1			201 (Alga, Growth
						Inhibition Test)

Persistence and degradability:

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
Cumene hydroperoxide 80-15-9			18 %	OECD Guideline 301 E (Ready biodegradability: Modified OECD Screening Test)
Cumene 98-82-8		aerobic	86 %	-
Ethane-1,2-diol 107-21-1	readily biodegradable	aerobic	83 - 96 %	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))

Bioaccumulative potential / Mobility in soil:

Hazardous components CAS-No.	LogKow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
Cumene hydroperoxide 80-15-9		9,1				OECD Guideline 305 (Bioconcentration: Flow- through Fish Test)
Cumene hydroperoxide 80-15-9	2,16					
Cumene 98-82-8		35,5		Carassius auratus		OECD Guideline 305 (Bioconcentration: Flow- through Fish Test)
Cumene 98-82-8	3,55				23 °C	OECD Guideline 107 (Partition Coefficient (noctanol / water), Shake Flask Method)
Ethane-1,2-diol 107-21-1	-1,36					,

MSDS-No.: 153640 Loctite 561 Page 8 of 9

V003.1

SECTION 13: Disposal considerations

Waste treatment methods:

Product disposal:

Dispose of in accordance with local and national regulations.

Contribution of this product to waste is very insignificant in comparison to article in which it is used

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

SECTION 14: Transport information

General information:

Not hazardous according to RID, ADR, ADNR, IMDG, IATA-DGR.

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture:

VOC content < 5 % (As defined in the Council Directive 2004/42/EC)

MSDS-No.: 153640 Loctite 561 Page 9 of 9

V003.1

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

R10 Flammable.

R21/22 Harmful in contact with skin and if swallowed.

R22 Harmful if swallowed.

R23 Toxic by inhalation.

R34 Causes burns.

R37 Irritating to respiratory system.

R48/20/22 Harmful: danger of serious damage to health by prolonged exposure through inhalation and if swallowed.

R51 Toxic to aquatic organisms.

R53 May cause long-term adverse effects in the aquatic environment.

R65 Harmful: may cause lung damage if swallowed.

R7 May cause fire.

H226 Flammable liquid and vapour.

H242 Heating may cause a fire.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H331 Toxic if inhaled.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

This safety data sheet was prepared in accordance with Council Directive 67/548/EEC and it's subsequent amendments, and Commission Directive 1999/45/EC.