

# Safety Data Sheet according to (EC) No 1907/2006

Page 1 of 8

Loctite 573

sds no. : 153496 V004.2 Revision: 19.05.2011 printing date: 08.06.2011

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier: Loctite 573 Relevant identified uses of the substance or mixture and uses advised against: Intended use: Anaerobic

### Details of the supplier of the safety data sheet:

Henkel Ireland Limited Product Safety & Regulatory Affairs Tallaght Business Park, Whitestown Dublin 24

#### Ireland

Phone: +353 (14046444) Fax-no.: +353 (14519926)

ua-productsafety.uk@uk.henkel.com

#### **Emergency telephone number:**

24 Hours Emergency Tel: +44 (0)1442 278497

## **SECTION 2: Hazards identification**

## Classification of the substance or mixture:

#### **Classification (DPD):**

The product is not subject to classification according to the calculation methods of the "General Classification Guideline for Preparations of the EC" as issued in the last version.

#### Label elements (DPD):

#### Risk phrases:

Not classified as hazardous.

### Other hazards:

None if used properly.

**SECTION 3: Composition/information on ingredients** 

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Cumene hydroperoxide	201-254-7	0,1- 1%	Acute toxicity 4; Dermal
80-15-9			H312
			Specific target organ toxicity - repeated
			exposure 2
			H373
			Acute toxicity 3; Inhalation
			H331
			Acute toxicity 4; Oral
			H302
			Organic peroxides E
			H242
			Chronic hazards to the aquatic environment 2
			H411
			Skin corrosion 1B
			H314
Cumene	202-704-5	0,1- 0,5 %	Flammable liquids 3
98-82-8			H226
			Aspiration hazard 1
			H304
			Specific target organ toxicity - single
			exposure 3
			H335
			Chronic hazards to the aquatic environment 2
			H411

Only dangerous ingredients for which a CLP classification is already available are displayed in this table. For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

Declaration of ingredients according to DPD (EC) No 1999/45:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Cumene hydroperoxide 80-15-9	201-254-7	0,1 - 1 %	T - Toxic; R23 Xn - Harmful; R21/22, R48/20/22 O - Oxidizing; R7 C - Corrosive; R34 N - Dangerous for the environment; R51, R53
Cumene 98-82-8	202-704-5	0,1 - 0,5 %	R10 Xn - Harmful; R65 Xi - Irritant; R37 N - Dangerous for the environment; R51, R53

For full text of the R-Phrases indicated by codes see section 16 'Other Information'. Substances without classification may have community workplace exposure limits available.

## **SECTION 4: First aid measures**

### Description of first aid measures:

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap. Seek medical advice.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

Ingestion:

Rinse out mouth, drink 1-2 glasses of water, do not induce vomiting. Seek medical advice.

### Most important symptoms and effects, both acute and delayed:

No particular measures required.

# Indication of any immediate medical attention and special treatment needed:

See section: Description of first aid measures

## **SECTION 5: Firefighting measures**

### Extinguishing media:

Suitable extinguishing media:

Carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons: None known

#### Special hazards arising from the substance or mixture:

None Oxides of carbon, oxides of nitrogen, irritating organic vapors. Sulphur oxides

#### Advice for firefighters:

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

## **SECTION 6: Accidental release measures**

### Personal precautions, protective equipment and emergency procedures:

Avoid skin and eye contact. Ensure adequate ventilation. See advice in chapter 8

### **Environmental precautions:**

Do not let product enter drains.

### Methods and material for containment and cleaning up:

For small spills wipe up with paper towel and place in container for disposal. For large spills absorb onto inert absorbent material and place in sealed container for disposal. Dispose of contaminated material as waste according to Chapter 13.

## **SECTION 7: Handling and storage**

#### Precautions for safe handling:

Use only in well-ventilated areas.

No particular measures required.

Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.

Use only in well-ventilated areas.

No particular measures required.

Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.

### Hygiene measures:

Good industrial hygiene practices should be observed.

### Conditions for safe storage, including any incompatibilities:

Store in original containers at 8-21°C (46.4-69.8°F) and do not return residual materials to containers as contamination may reduce the shelf life of the bulk product.

#### Specific end use(s):

Anaerobic

### **Control parameters:**

Valid for Great Britain

Basis

UK EH40 WELs

Ingredient	ppm	mg/m3	Туре	Category	Remarks
CUMENE	25	125	Time Weighted Average		EH40 WEL
98-82-8			(TWA):		
CUMENE	50	250	Short Term Exposure		EH40 WEL
98-82-8			Limit (STEL):		
CUMENE			Skin designation:	Can be absorbed through the	EH40 WEL
98-82-8			-	skin.	
CUMENE			Skin designation:	Can be absorbed through the	ECTLV
98-82-8			-	skin.	
CUMENE	50	250	Short Term Exposure	Indicative	ECTLV
98-82-8			Limit (STEL):		
CUMENE	20	100	Time Weighted Average	Indicative	ECTLV
98-82-8			(TWA):		

#### **Exposure controls:**

Respiratory protection:

Use only in well-ventilated areas.

### Hand protection:

The use of chemical resistant gloves such as Nitrile are recommended.

Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed then the gloves should be replaced.

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

#### Eye protection:

Wear protective glasses.

#### Skin protection:

Wear suitable protective clothing.

## **SECTION 9: Physical and chemical properties**

Information on basic physical and chemical prop	Information on basic physical and chemical properties:						
Appearance	paste						
	paste						
	green						
Odor	characteristic						
рН	3,00 - 6,00						
0							
Initial boiling point	> 150,0 °C (> 302 °F)						
Flash point	>100,0 °C (>212 °F)						
Decomposition temperature	No data available / Not applicable						
Vapour pressure	< 0,27 mbar						

Density	1,0800 g/cm3
() Declar de maiter	N. J. (
Bulk density	No data available / Not applicable
Viscosity	No data available / Not applicable
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Solubility (qualitative)	Not miscible
(Solvent: Water)	
Solidification temperature	No data available / Not applicable
Melting point	No data available / Not applicable
Flammability	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Explosive limits	No data available / Not applicable
Partition coefficient: n-octanol/water	No data available / Not applicable
Evaporation rate	No data available / Not applicable
Vapor density	No data available / Not applicable
Oxidising properties	No data available / Not applicable

#### Other information:

No data available / Not applicable

## **SECTION 10: Stability and reactivity**

#### **Reactivity:**

Reaction with strong acids. Reacts with strong oxidants.

### Chemical stability:

Stable under recommended storage conditions.

### Possibility of hazardous reactions:

See section reactivity

#### Conditions to avoid: Stable

## Incompatible materials:

No data available.

### Hazardous decomposition products:

carbon oxides. Sulphur oxides nitrogen oxides Irritating organic vapours.

## **SECTION 11: Toxicological information**

### General toxicological information:

The preparation is classified based on the conventional method outlined in Article 6(1)(a) of Directive 1999/45/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

#### **Oral toxicity:**

This material is considered to have low toxicity if swallowed.

#### Inhalative toxicity:

Inhalation of vapors in high concentration may cause irritation of respiratory system

#### Skin irritation:

Although it is not a common sensitizer there may be a risk of sensitization on prolonged or repeated contact with damaged skin

#### Eye irritation:

May cause mild irritation to the eyes.

### Acute toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Cumene hydroperoxide	LD50	550 mg/kg	oral		rat	
80-15-9	LC50	220 ppm	inhalation	4 h	rat	
	LD50	500 mg/kg	dermal		rat	

## Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Cumene hydroperoxide 80-15-9	corrosive		rabbit	

### Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Cumene hydroperoxide 80-15-9	positive	bacterial reverse mutation assay (e.g Ames test)	without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Cumene hydroperoxide 80-15-9	negative	dermal		mouse	

## **SECTION 12: Ecological information**

## General ecological information:

Cured Loctite products are typical polymers and do not pose any immediate environmental hazards. The preparation is classified based on the conventional method outlined in Article 6(1)(a) of Directive 1999/45/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

### **Ecotoxicity:**

Do not empty into drains / surface water / ground water.

### Mobility:

Cured adhesives are immobile.

#### Persistence and Biodegradability:

The product is not biodegradable.

#### **Bioaccumulative potential:**

Does not bioaccumulate.

## Toxicity:

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
Cumene hydroperoxide 80-15-9	LC50	3,9 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute
Cumene hydroperoxide 80-15-9	EC50	18 mg/l	Daphnia	48 h	Daphnia magna	Toxicity Test) OECD Guideline 202 (Daphnia sp. Acute Immobilisation
Cumene hydroperoxide 80-15-9	ErC50	3,1 mg/l	Algae	72 h	Pseudokirchnerella subcapitata	Test) OECD Guideline 201 (Alga, Growth
Cumene 98-82-8	LC50	4,8 mg/l	Fish	96 h	Oncorhynchus mykiss	Inhibition Test) OECD Guideline 203 (Fish, Acute
Cumene 98-82-8	EC50	4 mg/l	Daphnia	48 h	Daphnia magna	Toxicity Test) OECD Guideline 202 (Daphnia sp. Acute
Cumene 98-82-8	EC50	2,6 mg/l	Algae	72 h	Selenastrum capricornutum (new name: Pseudokirchnerella subcapitata)	Immobilisation Test) OECD Guideline 201 (Alga, Growth Inhibition Test)

## Persistence and degradability:

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
Cumene hydroperoxide 80-15-9		appication	18 %	OECD Guideline 301 E (Ready biodegradability: Modified OECD Screening Test)
Cumene 98-82-8		aerobic	86 %	

## Bioaccumulative potential / Mobility in soil:

Hazardous components CAS-No.	LogKow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
Cumene hydroperoxide 80-15-9		9,1				OECD Guideline 305 (Bioconcentration: Flow- through Fish Test)
Cumene hydroperoxide 80-15-9	2,16					
Cumene 98-82-8		35,5		Carassius auratus		OECD Guideline 305 (Bioconcentration: Flow- through Fish Test)
Cumene 98-82-8	3,55				23 °C	OECD Guideline 107 (Partition Coefficient (n- octanol / water), Shake Flask Method)

## **SECTION 13: Disposal considerations**

### Waste treatment methods:

## Product disposal:

Dispose of in accordance with local and national regulations.

Contribution of this product to waste is very insignificant in comparison to article in which it is used

### Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

#### Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

## **SECTION 14: Transport information**

## General information:

Not hazardous according to RID, ADR, ADNR, IMDG, IATA-DGR.

## **SECTION 15: Regulatory information**

Safety, health and environmental regulations/legislation specific for the substance or mixture:

VOC content (1999/13/EC) < 5,00 %

## **SECTION 16: Other information**

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

R10 Flammable.

R21/22 Harmful in contact with skin and if swallowed.

R23 Toxic by inhalation.

R34 Causes burns.

R37 Irritating to respiratory system.

R48/20/22 Harmful: danger of serious damage to health by prolonged exposure through inhalation and if swallowed.

R51 Toxic to aquatic organisms.

R53 May cause long-term adverse effects in the aquatic environment.

R65 Harmful: may cause lung damage if swallowed.

R7 May cause fire.

H226 Flammable liquid and vapour.

H242 Heating may cause a fire.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H331 Toxic if inhaled.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

### Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

This safety data sheet was prepared in accordance with Council Directive 67/548/EEC and it's subsequent amendments, and Commission Directive 1999/45/EC.