

# Safety Data Sheet according to (EC) No 1907/2006

Page 1 of 10

sds no.: 153473 V002.1

Revision: 20.04.2011

printing date: 08.06.2011

Loctite 638

\_\_\_\_\_\_

## 1. Identification of the substance/mixture and of the company/undertaking

#### **Product identifier:**

Loctite 638

## Relevant identified uses of the substance or mixture and uses advised against:

Intended use: Anaerobic

## Details of the supplier of the safety data sheet:

Henkel Ireland Limited Product Safety & Regulatory Affairs Tallaght Business Park, Whitestown Dublin 24

Ireland

Phone: +353 (14046444) Fax-no.: +353 (14519926)

ua-products a fety. uk @uk.henkel.com

#### **Emergency telephone number:**

24 Hours Emergency Tel: +44 (0)1442 278497

## 2. Hazards identification

## Classification of the substance or mixture:

## Classification (DPD):

Sensitizing

R43 May cause sensitisation by skin contact.

Xi - Irritant

R37/38 Irritating to respiratory system and skin.

R41 Risk of serious damage to eyes.

MSDS-No.: 153473 Loctite 638 Page 2 of 10

V002.1

## Label elements (DPD):

#### Xi - Irritant



#### Risk phrases:

R37/38 Irritating to respiratory system and skin.

R41 Risk of serious damage to eyes.

R43 May cause sensitisation by skin contact.

## Safety phrases:

S24/25 Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S28 After contact with skin, wash immediately with plenty of water and soap.

S37/39 Wear suitable gloves and eye/face protection.

S51 Use only in well-ventilated areas.

#### Additional labeling:

For consumer use only: S2 Keep out of the reach of children

S46 If swallowed, seek medical advice immediately and show this container or label.

#### Contains:

Hydroxypropyl methacrylate,

Acrylic acid,

Cumene hydroperoxide,

Methacrylic acid

#### Other hazards:

May produce an allergic reaction.

Non corrosive to skin in accordance with the invitro test method, B40 skin corrosion - Human skin model assay, specified in Part B of Annex V to Directive 67/548/EEC.

## 3. Composition/information on ingredients

## General chemical description:

Methacrylate resin based product containing Acrylic Acid

MSDS-No.: 153473 Loctite 638 Page 3 of 10

V002.1

## Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Acrylic acid 79-10-7	201-177-9	>= 5-< 10 %	Acute toxicity 4; Oral H302
			Skin corrosion 1A
			H314
			Flammable liquids 3
			H226
			Acute toxicity 4; Dermal H312
			Acute hazards to the aquatic environment 1 H400
			Acute toxicity 4; Inhalation H332
Cumene hydroperoxide	201-254-7	>= 1-< 2,5 %	Acute toxicity 4; Dermal
80-15-9			H312
			Specific target organ toxicity - repeated
			exposure 2
			H373
			Acute toxicity 3; Inhalation H331
			Acute toxicity 4; Oral
			H302
			Organic peroxides E
			H242
			Chronic hazards to the aquatic environment 2 H411
			Skin corrosion 1B
			H314
Methacrylic acid	201-204-4	>= 1-< 5 %	Acute toxicity 4; Oral
79-41-4			H302
			Skin corrosion 1A
			H314
			Acute toxicity 4; Dermal
2-Hydroxyethyl methacrylate	212-782-2	>= 0,1-< 1 %	H312 Serious eye irritation 2
868-77-9	212-702-2	>= 0,1-< 1 %	H319
808-77-9			Skin irritation 2
			H315
			Skin sensitizer 1
			H317
Cumene	202-704-5	>= 0-< 2,5 %	Flammable liquids 3
98-82-8			H226
			Aspiration hazard 1
			H304
			Specific target organ toxicity - single
			exposure 3
			H335
			Chronic hazards to the aquatic environment 2
			H411

Only dangerous ingredients for which a CLP classification is already available are displayed in this table. For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

MSDS-No.: 153473 Loctite 638 Page 4 of 10

V002.1

## Declaration of ingredients according to DPD (EC) No 1999/45:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Hydroxypropyl methacrylate 27813-02-1	248-666-3	>= 25 - < 50 %	Xi - Irritant; R36, R43
Acrylic acid 79-10-7	201-177-9	>= 5 - < 10 %	Xn - Harmful; R20/21/22 R10 C - Corrosive; R35 N - Dangerous for the environment; R50
Cumene hydroperoxide 80-15-9	201-254-7	>= 1 -< 2,5 %	T - Toxic; R23 Xn - Harmful; R21/22, R48/20/22 O - Oxidizing; R7 C - Corrosive; R34 N - Dangerous for the environment; R51, R53
Methacrylic acid 79-41-4	201-204-4	>= 1 - < 5 %	C - Corrosive; R35 Xn - Harmful; R21/22
2-Hydroxyethyl methacrylate 868-77-9	212-782-2	>= 0,1 -< 1 %	Xi - Irritant; R36/38 R43
Cumene 98-82-8	202-704-5	>= 0 -< 2,5 %	R10 Xn - Harmful; R65 Xi - Irritant; R37 N - Dangerous for the environment; R51, R53

For full text of the R-Phrases indicated by codes see section 16 'Other Information'. Substances without classification may have community workplace exposure limits available.

## 4. First aid measures

#### Description of first aid measures:

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact

Rinse with running water and soap.

Seek medical advice.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

Ingestion:

Rinse out mouth, drink 1-2 glasses of water, do not induce vomiting.

Seek medical advice.

Most important symptoms and effects, both acute and delayed:

SKIN: Redness, inflammation.

EYE: Irritation, conjunctivitis.

SKIN: Rash, Urticaria.

Indication of any immediate medical attention and special treatment needed:

See section: Description of first aid measures

# 5. Firefighting measures

Extinguishing media:

Suitable extinguishing media:

Carbon dioxide, foam, powder

Special hazards arising from the substance or mixture:

Oxides of carbon, oxides of nitrogen, irritating organic vapors. Sulphur oxides

MSDS-No.: 153473 Loctite 638 Page 5 of 10

V002.1

### Advice for firefighters:

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

## 6. Accidental release measures

## Personal precautions, protective equipment and emergency procedures:

Avoid skin and eye contact.

#### **Environmental precautions:**

Do not let product enter drains.

## Methods and material for containment and cleaning up:

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

#### Reference to other sections:

See advice in chapter 8

## 7. Handling and storage

## Precautions for safe handling:

Use only in well-ventilated areas.

Avoid skin and eye contact.

Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.

#### Hygiene measures:

Good industrial hygiene practices should be observed.

## Conditions for safe storage, including any incompatibilities:

Store in original containers at  $8-21^{\circ}$ C ( $46.4-69.8^{\circ}$ F) and do not return residual materials to containers as contamination may reduce the shelf life of the bulk product.

#### **Specific end use(s):**

Anaerobic

## 8. Exposure controls/personal protection

#### **Control parameters:**

Valid for

Great Britain

Ingredient	ppm	mg/m <sup>3</sup>	Type	Category	Remarks
METHACRYLIC ACID	40	143	Short Term Exposure		EH40 WEL
79-41-4			Limit (STEL):		
METHACRYLIC ACID	20	72	Time Weighted Average		EH40 WEL
79-41-4			(TWA):		
CUMENE	25	125	Time Weighted Average		EH40 WEL
98-82-8			(TWA):		
CUMENE	50	250	Short Term Exposure		EH40 WEL
98-82-8			Limit (STEL):		
CUMENE			Skin designation:	Can be absorbed through the	EH40 WEL
98-82-8				skin.	
CUMENE			Skin designation:	Can be absorbed through the	ECTLV
98-82-8				skin.	
CUMENE	50	250	Short Term Exposure	Indicative	ECTLV
98-82-8			Limit (STEL):		
CUMENE	20	100	Time Weighted Average	Indicative	ECTLV
98-82-8			(TWA):		

#### **Exposure controls:**

MSDS-No.: 153473 Loctite 638 Page 6 of 10

V002.1

### Respiratory protection:

Use only in well-ventilated areas.

#### Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Wear protective glasses.

Skin protection:

Wear suitable protective clothing.

## 9. Physical and chemical properties

#### Information on basic physical and chemical properties:

Appearance liquid green
Odor irritating

pH No data available / Not applicable

 $\begin{array}{ll} \mbox{Initial boiling point} & > 100,0 \ ^{\circ}\mbox{C} \ (> 212 \ ^{\circ}\mbox{F}) \\ \mbox{Flash point} & > 93,3 \ ^{\circ}\mbox{C} \ (> 199.94 \ ^{\circ}\mbox{F}) \end{array}$ 

Decomposition temperature No data available / Not applicable

Vapour pressure < 4,0000000 mbar

(20 °C (68 °F))

Density 1,0500 g/cm3

0

Bulk density

No data available / Not applicable
Viscosity

No data available / Not applicable
Viscosity (kinematic)

Explosive properties

No data available / Not applicable
No data available / Not applicable

Solubility (qualitative) Miscible

(Solvent: Acetone)

Solidification temperature No data available / Not applicable No data available / Not applicable Melting point Flammability No data available / Not applicable Auto-ignition temperature No data available / Not applicable Explosive limits No data available / Not applicable Partition coefficient: n-octanol/water No data available / Not applicable Evaporation rate No data available / Not applicable No data available / Not applicable Vapor density No data available / Not applicable Oxidising properties

#### Other information:

No data available / Not applicable

## 10. Stability and reactivity

#### Reactivity:

Reaction with strong acids. Reacts with strong oxidants. MSDS-No.: 153473 Loctite 638 Page 7 of 10

V002.1

#### Chemical stability:

Stable under recommended storage conditions.

#### Possibility of hazardous reactions:

See section reactivity

#### Conditions to avoid:

Stable

## 11. Toxicological information

#### General toxicological information:

The preparation is classified based on the conventional method outlined in Article 6(1)(a) of Directive 1999/45/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

## Oral toxicity:

This material is considered to have low toxicity if swallowed.

May cause irritation to the digestive tract.

## Inhalative toxicity:

Irritating to respiratory system

## Skin irritation:

Irritating to the skin.

#### Eye irritation:

Risk of serious damage to eyes

## Sensitizing:

May cause sensitization by skin contact.

## Acute toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Methacrylic acid 79-41-4	LC50	7,1 mg/l	inhalation	4 h	rat	

## Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
Methacrylic acid 79-41-4	not sensitising	Buehler test	guinea pig	

#### Germ cell mutagenicity:

Hazardous components	Result	Type of study /	Metabolic	Species	Method
CAS-No.		Route of	activation /		
		administration	Exposure time		
Acrylic acid	negative	bacterial reverse	with and without		
79-10-7	_	mutation assay (e.g			
		Ames test)			
2-Hydroxyethyl	negative	bacterial reverse	with and without		OECD Guideline 471
methacrylate	positive	mutation assay (e.g	with and without		(Bacterial Reverse Mutation
868-77-9		Ames test)			Assay)
		in vitro mammalian			OECD Guideline 473 (In vitro
		chromosome			Mammalian Chromosome
		aberration test			Aberration Test)

MSDS-No.: 153473 Loctite 638 Page 8 of 10

V002.1

## 12. Ecological information

# General ecological information:

Do not empty into drains / surface water / ground water.

Precautions required with respect to Environmental Hazards of articles in which this product is used should be considered. The preparation is classified based on the conventional method outlined in Article 6(1)(a) of Directive 1999/45/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

# **Toxicity:**

Hazardous components	Value	Value	Acute	Exposure	Species	Method
CAS-No.	type		Toxicity	time		
Hydroxypropyl methacrylate	LC50	493 mg/l	Study Fish	48 h	Leuciscus idus melanotus	
27813-02-1	LC30	475 Hig/1	1 1511	40 11	Leuciscus idus incianotus	
Acrylic acid	LC50	27 mg/l	Fish	96 h	Salmo gairdneri (new name:	OECD Guideline
79-10-7					Oncorhynchus mykiss)	203 (Fish, Acute
Acrylic acid	EC50	47 mg/l	Daphnia	48 h	Daphnia magna	Toxicity Test) OECD Guideline
79-10-7		.,8	F			202 (Daphnia sp.
						Acute
						Immobilisation Test)
Acrylic acid	EC50	0,04 mg/l	Algae	72 h	Scenedesmus subspicatus (new	OECD Guideline
79-10-7		, ,			name: Desmodesmus	201 (Alga, Growth
Common bodon monerida	1.050	2.0 /1	Eak	061	subspicatus)	Inhibition Test)
Cumene hydroperoxide 80-15-9	LC50	3,9 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute
						Toxicity Test)
Cumene hydroperoxide	EC50	18 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline
80-15-9						202 (Daphnia sp. Acute
						Immobilisation
						Test)
Cumene hydroperoxide 80-15-9	ErC50	3,1 mg/l	Algae	72 h	Pseudokirchnerella subcapitata	OECD Guideline 201 (Alga, Growth
80-13-9						Inhibition Test)
Methacrylic acid	LC50	100 - 180 mg/l	Fish	96 h	Brachydanio rerio (new name:	OECD Guideline
79-41-4					Danio rerio)	203 (Fish, Acute
Methacrylic acid	EC50	> 130 mg/l	Daphnia	48 h	Daphnia magna	Toxicity Test) OECD Guideline
79-41-4	LCSO	> 150 mg/1	Барина	40 11	Варина надна	202 (Daphnia sp.
						Acute
						Immobilisation Test)
Methacrylic acid	EC50	> 8,2 mg/l	Algae			OECD Guideline
79-41-4		, ,				201 (Alga, Growth
2 11-1	1.050	227 //	F21.	061	D'	Inhibition Test)
2-Hydroxyethyl methacrylate 868-77-9	LC50	227 mg/l	Fish	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute
000 77 9						Toxicity Test)
2-Hydroxyethyl methacrylate	EC50	380 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline
868-77-9						202 (Daphnia sp. Acute
						Immobilisation
						Test)
2-Hydroxyethyl methacrylate 868-77-9	EC50	345 mg/l	Algae	72 h	Selenastrum capricornutum	OECD Guideline
868-77-9					(new name: Pseudokirchnerella subcapitata)	201 (Alga, Growth Inhibition Test)
Cumene	LC50	4,8 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline
98-82-8						203 (Fish, Acute
Cumene	EC50	4 mg/l	Daphnia	48 h	Daphnia magna	Toxicity Test) OECD Guideline
98-82-8	LCJU	7 mg/1	Барина	70 11	Dapinna magna	202 (Daphnia sp.
						Acute
						Immobilisation Test)
Cumene	EC50	2,6 mg/l	Algae	72 h	Selenastrum capricornutum	OECD Guideline
98-82-8		-,~ <del>o</del> -	8		(new name: Pseudokirchnerella	201 (Alga, Growth
			]	<u> </u>	subcapitata)	Inhibition Test)

MSDS-No.: 153473 Loctite 638 Page 9 of 10

V002.1

## Persistence and degradability:

Hazardous components	Result	Route of	Degradability	Method
CAS-No.		application		
Hydroxypropyl methacrylate	readily biodegradable	aerobic	94,2 %	OECD Guideline 301 E (Ready
27813-02-1				biodegradability: Modified OECD
				Screening Test)
Acrylic acid	readily biodegradable	aerobic	81 %	OECD Guideline 301 D (Ready
79-10-7				Biodegradability: Closed Bottle
				Test)
Cumene hydroperoxide			18 %	OECD Guideline 301 E (Ready
80-15-9				biodegradability: Modified OECD
				Screening Test)
Methacrylic acid	readily biodegradable	aerobic	86 %	OECD Guideline 301 D (Ready
79-41-4				Biodegradability: Closed Bottle
				Test)
2-Hydroxyethyl methacrylate	readily biodegradable	aerobic	98 %	OECD Guideline 301 E (Ready
868-77-9				biodegradability: Modified OECD
				Screening Test)
Cumene		aerobic	86 %	
98-82-8				

## Bioaccumulative potential / Mobility in soil:

Hazardous components CAS-No.	LogKow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
Hydroxypropyl methacrylate 27813-02-1	0,97					
Acrylic acid 79-10-7	0,46				25 °C	OECD Guideline 107 (Partition Coefficient (noctanol / water), Shake Flask Method)
Cumene hydroperoxide 80-15-9		9,1				OECD Guideline 305 (Bioconcentration: Flow- through Fish Test)
Cumene hydroperoxide 80-15-9	2,16					
Methacrylic acid 79-41-4	0,93					
Cumene 98-82-8		35,5		Carassius auratus		OECD Guideline 305 (Bioconcentration: Flow- through Fish Test)
Cumene 98-82-8	3,55				23 °C	OECD Guideline 107 (Partition Coefficient (noctanol / water), Shake Flask Method)

## 13. Disposal considerations

#### Waste treatment methods:

Product disposal:

Dispose of in accordance with local and national regulations.

Contribution of this product to waste is very insignificant in comparison to article in which it is used

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

## 14. Transport information

## General information:

Not hazardous according to RID, ADR, ADNR, IMDG, IATA-DGR.

MSDS-No.: 153473 Loctite 638 Page 10 of 10

V002.1

## 15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture:

VOC content < 5 % (1999/13/EC)

## 16. Other information

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

R10 Flammable.

R20/21/22 Harmful by inhalation, in contact with skin and if swallowed.

R21/22 Harmful in contact with skin and if swallowed.

R23 Toxic by inhalation.

R34 Causes burns.

R35 Causes severe burns.

R36 Irritating to eyes.

R36/38 Irritating to eyes and skin.

R37 Irritating to respiratory system.

R43 May cause sensitisation by skin contact.

R48/20/22 Harmful: danger of serious damage to health by prolonged exposure through inhalation and if swallowed.

R50 Very toxic to aquatic organisms.

R51 Toxic to aquatic organisms.

R53 May cause long-term adverse effects in the aquatic environment.

R65 Harmful: may cause lung damage if swallowed.

R7 May cause fire.

H226 Flammable liquid and vapour.

H242 Heating may cause a fire.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

#### **Further information:**

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

This safety data sheet was prepared in accordance with Council Directive 67/548/EEC and it's subsequent amendments, and Commission Directive 1999/45/EC.