

Safety Data Sheet according to (EC) No 1907/2006

Page 1 of 10

Loctite 7061

sds no. : 232327 V004.0 Revision: 07.01.2011 printing date: 09.06.2011

1. Identification of the substance/mixture and of the company/undertaking

Product identifier: Loctite 7061 Relevant identified uses of the substance or mixture and uses advised against: Intended use: Cleaner

Details of the supplier of the safety data sheet:

Henkel Ireland Limited Product Safety & Regulatory Affairs Tallaght Business Park, Whitestown Dublin 24

Ireland

Phone: +353 (14046444) Fax-no.: +353 (14519926)

ua-productsafety.uk@uk.henkel.com

Emergency telephone number:

24 Hours Emergency Tel: +44 (0)1442 278497

2. Hazards identification

Classification of the substance or mixture:

Classification (DPD):

Xi - Irritant

R36 Irritating to eyes.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

F+ - Extremely flammable

R12 Extremely flammable.

Label elements (DPD):

Xi - Irritant

F+ - Extremely flammable



Risk phrases:

R12 Extremely flammable.

R36 Irritating to eyes.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

Safety phrases:

S16 Keep away from sources of ignition - No smoking.

S23 Do not breathe vapour.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S37 Wear suitable gloves.

S61 Avoid release to the environment. Refer to special instructions/Safety data sheets.

Additional labeling:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children

For consumer use only: S2 Keep out of the reach of children

S46 If swallowed, seek medical advice immediately and show this container or label.

Other hazards:

The aerosol container is under pressure. Do not expose to high temperatures.

3. Composition/information on ingredients

General chemical description:

Cleaner

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Acetone 67-64-1	200-662-2	60- 80 %	Flammable liquids 2 H225 Specific target organ toxicity - single exposure 3 H336 Serious eye irritation 2 H319
Ethanol denatured 64-17-5	200-578-6	20- 40 %	Flammable liquids 2 H225
Propan-2-ol 67-63-0	200-661-7	1- 5%	Specific target organ toxicity - single exposure 3 H336 Flammable liquids 2 H225 Serious eye irritation 2 H319

Only dangerous ingredients for which a CLP classification is already available are displayed in this table. For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

Declaration of ingredients according to DPD (EC) No 1999/45:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Acetone 67-64-1	200-662-2	60 - 80 %	R66 Xi - Irritant; R36 F - Highly flammable; R11 R67
Ethanol denatured 64-17-5	200-578-6	20 - 40 %	F - Highly flammable; R11
Propan-2-ol 67-63-0	200-661-7	1 - 5 %	Xi - Irritant; R36 F - Highly flammable; R11 R67
Carbon dioxide 124-38-9	204-696-9	5 - 10 %	

For full text of the R-Phrases indicated by codes see section 16 'Other Information'. Substances without classification may have community workplace exposure limits available.

4. First aid measures

Description of first aid measures:

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap. Seek medical advice.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

Ingestion:

Rinse out mouth, drink 1-2 glasses of water, do not induce vomiting. Seek medical advice.

Most important symptoms and effects, both acute and delayed:

Vapors may cause drowsiness and dizziness.

Indication of any immediate medical attention and special treatment needed:

See section: Description of first aid measures

5. Firefighting measures

Extinguishing media:

Suitable extinguishing media: Carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

None known

None

Special hazards arising from the substance or mixture:

Oxides of carbon, oxides of nitrogen, irritating organic vapors.

Advice for firefighters:

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Avoid skin and eye contact. Ensure adequate ventilation. See advice in chapter 8

Environmental precautions:

Do not let product enter drains.

Methods and material for containment and cleaning up:

For small spills wipe up with paper towel and place in container for disposal. For large spills absorb onto inert absorbent material and place in sealed container for disposal. Dispose of contaminated material as waste according to Chapter 13.

7. Handling and storage

Precautions for safe handling:

Use only in well-ventilated areas. Vapours should be extracted to avoid inhalation. Keep away from sources of ignition - no smoking.

Hygiene measures:

Good industrial hygiene practices should be observed.

Conditions for safe storage, including any incompatibilities:

Store in a cool, well-ventilated place. Keep away from heat and direct sunlight.

Specific end use(s):

Cleaner

8. Exposure controls/personal protection

Control parameters:

Valid for

Great Britain

Basis UK EH40 WELs

Ingredient	ppm	mg/m3	Туре	Category	Remarks
ACETONE	1.500	3.620	Short Term Exposure		EH40 WEL
67-64-1			Limit (STEL):		
ACETONE	500	1.210	Time Weighted Average		EH40 WEL
67-64-1			(TWA):		
ACETONE	500	1.210	Time Weighted Average	Indicative	ECTLV
67-64-1			(TWA):		
CARBON DIOXIDE	15.000	27.400	Short Term Exposure		EH40 WEL
124-38-9			Limit (STEL):		
CARBON DIOXIDE	5.000	9.150	Time Weighted Average		EH40 WEL
124-38-9			(TWA):		
CARBON DIOXIDE	5.000	9.000	Time Weighted Average	Indicative	ECTLV
124-38-9			(TWA):		
ETHANOL	1.000	1.920	Time Weighted Average		EH40 WEL
64-17-5			(TWA):		
PROPAN-2-OL	400	999	Time Weighted Average		EH40 WEL
67-63-0			(TWA):		
PROPAN-2-OL	500	1.250	Short Term Exposure		EH40 WEL
67-63-0			Limit (STEL):		

Exposure controls:

Respiratory protection:

Use only in well-ventilated areas.

Hand protection:

Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed then the gloves should be replaced.

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Wear protective glasses.

Skin protection:

Wear suitable protective clothing.

9. Physical and chemical properties

Pungent

Information on basic physical and chemical properties:					
Appearance	liquid				
	colourless				

Odor

	. 1. 1.1
pH	not applicable
Initial boiling point	Not determined
Flash point	Not applicable to aerosols.
Decomposition temperature	No data available / Not applicable
Vapour pressure	Not determined
Density	0,68 g/cm3
(20 °C (68 °F))	
Bulk density	No data available / Not applicable
Viscosity	No data available / Not applicable
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Solubility (qualitative)	Miscible
(Solvent: Water)	
Solubility (qualitative)	Miscible
(Solvent: Acetone)	
Solidification temperature	No data available / Not applicable
Melting point	No data available / Not applicable
Flammability	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Explosive limits	No data available / Not applicable
Partition coefficient: n-octanol/water	No data available / Not applicable
Evaporation rate	No data available / Not applicable
Vapor density	No data available / Not applicable
Oxidising properties	No data available / Not applicable

Other information:

No data available / Not applicable

10. Stability and reactivity

Reactivity:

Reaction with strong acids. Reacts with strong oxidants. Stable under recommended storage conditions.

Possibility of hazardous reactions:

See section reactivity

Conditions to avoid: Stable

Incompatible materials:

No data available.

Hazardous decomposition products:

Irritating organic vapours.

11. Toxicological information

General toxicological information:

The preparation is classified based on the conventional method outlined in Article 6(1)(a) of Directive 1999/45/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

Oral toxicity:

This material is considered to have low toxicity if swallowed.

Inhalative toxicity:

May cause headache and dizziness.

Skin irritation:

Solvent may remove essential oils from the skin making it susceptible to attack from other chemicals.

Eye irritation:

Irritating to eyes.

Acute toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Acetone 67-64-1	LD50 LC50 LD50	5.800 mg/kg 76 mg/l > 15.688 mg/kg	oral inhalation dermal	4 h	rat rat rabbit	
Ethanol denatured 64-17-5	LD50 LC50 LDLo	13.700 mg/kg 124,7 mg/l 20.000 mg/kg	oral inhalation dermal	4 h	rat rat rabbit	
Propan-2-ol 67-63-0	LD50 LC50 LD50	5.338 mg/kg 72,6 mg/l 12.870 mg/kg	oral inhalation dermal	4 h	rat rat rabbit	

Skin corrosion/irritation:

Hazardous components	Result	Exposure	Species	Method
CAS-No.		time		
Ethanol denatured	not irritating		rabbit	OECD Guideline 404 (Acute
64-17-5	-			Dermal Irritation / Corrosion)
Propan-2-ol	slightly irritating	4 h	rabbit	OECD Guideline 404 (Acute
67-63-0				Dermal Irritation / Corrosion)

Serious eye damage/irritation:

Hazardous components	Result	Exposure	Species	Method
CAS-No.		time		
Acetone	not irritating		rabbit	OECD Guideline 405 (Acute
67-64-1				Eye Irritation / Corrosion)
Ethanol denatured	not irritating		rabbit	OECD Guideline 405 (Acute
64-17-5				Eye Irritation / Corrosion)
Propan-2-ol	not irritating		rabbit	OECD Guideline 405 (Acute
67-63-0	-			Eye Irritation / Corrosion)

Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
Ethanol denatured 64-17-5	not sensitising	Guinea pig maximisat ion test	guinea pig	
Propan-2-ol 67-63-0	not sensitising	Buehler test	guinea pig	

Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Acetone 67-64-1	negative	bacterial forward mutation assay	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Ethanol denatured 64-17-5	negative negative	in vitro mammalian chromosome aberration test bacterial forward mutation assay	without with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Propan-2-ol 67-63-0	negative	bacterial forward mutation assay	with and without		

Repeated dose toxicity

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
Acetone 67-64-1	NOAEL=2500 ppm	oral: drinking water	13 weeks	rat	
Propan-2-ol 67-63-0	NOAEL=1500	inhalation	13 weeks 6 hours/day, 5 days/week	mouse	

12. Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

The preparation is classified based on the conventional method outlined in Article 6(1)(a) of Directive 1999/45/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

Mobility:

The product evaporates readily.

Persistence and Biodegradability:

No data available.

Bioaccumulative potential:

No data available.

Toxicity:

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
Acetone 67-64-1	LC50	8.120 mg/l	Fish	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute
	ECTO	C 000 4 4	D 1 .	40.1	D 1 .	Toxicity Test)
Acetone 67-64-1	EC50	6.098,4 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp.
07 01 1						Acute
						Immobilisation
						Test)
Ethanol denatured	LC50	14,2 g/l	Fish	96 h	Pimephales promelas	OECD Guideline
64-17-5						203 (Fish, Acute
Ethanol denatured	EC50	9.268 - 14.221 mg/l	Daphnia	48 h	Daphnia magna	Toxicity Test) OECD Guideline
64-17-5	LC50).200 - 14.221 mg/1	Dapinna	40 11	Dapinia magna	202 (Daphnia sp.
						Acute
						Immobilisation
						Test)
Ethanol denatured	EC50	> 5.000 mg/l	Algae	7 d	Scenedesmus quadricauda	OECD Guideline
64-17-5						201 (Alga, Growth
Propan-2-ol	LC50	9.640 mg/l	Fish	96 h	Pimephales promelas	Inhibition Test) OECD Guideline
67-63-0	LC50	9.040 mg/1	1480	90 II	r intepliales prometas	203 (Fish, Acute
07 05 0						Toxicity Test)
Propan-2-ol	EC50	13.299 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline
67-63-0		0				202 (Daphnia sp.
						Acute
						Immobilisation
	5050	1.000 /		0.61		Test)
Propan-2-ol	EC50	> 1.000 mg/l	Algae	96 h	Scenedesmus subspicatus (new	OECD Guideline
67-63-0					name: Desmodesmus subspicatus)	201 (Alga, Growth Inhibition Test)
	1		I	1	subspicatus)	minoruon rest)

Persistence and degradability:

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
Acetone 67-64-1	readily biodegradable	aerobic	81 - 92 %	EU Method C.4-E (Determination of the "Ready" BiodegradabilityClosed Bottle Test)
Ethanol denatured 64-17-5	readily biodegradable	aerobic	80 - 85 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Propan-2-ol 67-63-0	readily biodegradable	aerobic	95 %	OECD Guideline 301 E (Ready biodegradability: Modified OECD Screening Test)

Bioaccumulative potential / Mobility in soil:

Hazardous components CAS-No.	LogKow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
Acetone 67-64-1	0,24					
Ethanol denatured 64-17-5	-0,31					
Propan-2-ol 67-63-0	0,05					OECD Guideline 107 (Partition Coefficient (n- octanol / water), Shake Flask Method)

13. Disposal considerations

Waste treatment methods:

Product disposal:

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages: Disposal must be made according to official regulations.

Waste code

14 06 03 Other solvents and solvent mixtures

14. Transport information

Road transport ADR:

Class:	2		
Packaging group: Classification code:	5F		
Hazard ident. number:	51		
UN no.:	1950		
Label:	2.1		
Technical name:	AEROSOLS		
Tunnelcode:	(D)		
Railroad transport RID:			
Class:	2		
Packaging group:			
Classification code:	5F		
Hazard ident. number:	23		
UN no.:	1950		
Label:	2.1		
Technical name:	AEROSOLS		
Tunnelcode:			
Inland water transport ADN:			
Class:	2		
Packaging group:			
Classification code:	5F		
Hazard ident. number:			
UN no.:	1950		
Label:	2.1		
Technical name:	AEROSOLS		
Marine transport IMDG:			
Class:	2.1		
Packaging group:			
UN no.:	1950		
Label:	2.1		
EmS:	F-D ,S-U		
Seawater pollutant:	-		
Proper shipping name:	AEROSOLS		
Air transport IATA:			
Class:	2.1		
Packaging group:			
Packaging instructions (passenger)	203		
Packaging instructions (cargo)	203		
UN no.:	1950		
Label:	2.1		
Proper shipping name:	Aerosols, flammable		

15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture:

VOC content (1999/13/EC) 92,5 %

16. Other information

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

R11 Highly flammable.

R36 Irritating to eyes.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

H225Highly flammable liquid and vapour.

H319Causes serious eye irritation.

H336May cause drowsiness or dizziness.

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

This safety data sheet was prepared in accordance with Council Directive 67/548/EEC and it's subsequent amendments, and Commission Directive 1999/45/EC.