



AMBERKLENE FG

BIODEGRADABLE SOLVENT DEGREASER

Amberklene FG is a medium/ slower evaporation solvent degreaser that penetrates quickly and removes dirt and humidity, specially designed for use on food processing and packaging equipment. Can be used to remove grease and oils, lubricants, tar and adhesives, from bearings, housings, conveyor drives, chains and even wax-based anti-corrosion coatings.

Amberklene FG is an innovative solvent blend without chlorinated solvents or ozone-depleting components.

Authorised for use in inedible product processing, non-processing and exterior areas, is a neutral product, non-staining and does not contain water, nut oils or nut oil derivatives. The controlled evaporation rate ensures maximum contact time with contamination.



Cleaners



360° Spray System for all angle use



NSF Registered category:
Aerosol: A8 + C1, no 137996
Bulk: A8 + C1, no 140261



Just one of over 25 FG products

PRODUCT CODES / FILL SIZES



30242 / 500ml



30250 / 5Ltr

APPLICATIONS

Effective removal of grease, oil, dirt and other contaminants from:

- Motors
- Mechanical brakes and clutches
- Dies
- Pumps
- Chains
- Moulds
- Generators
- Sprockets
- Air tools
- Wire ropes
- Material handling equipment

DIRECTIONS

- Check solvent compatibility for your application prior to use. If in doubt, test on a small area.
- Use with adequate ventilation. Do not use on energised (live) equipment.
- Apply liberally and allow excess to run off, taking care to minimize contamination risk.
- Air dry or wipe with absorbent cloth.
- Repeat if necessary.
- Allow to dry thoroughly and vent before reactivating system.
- After application, re-lubricate moving parts.
- If parts or equipment are intended to return to a food processing area, rinsing with potable water is required.

TECHNICAL DATA (WITHOUT PROPELLANT)

Appearance	Colourless Liquid
Specific Gravity (@ 20°C)	0.78
Flash Point (closed cup)	40°C
Boiling Range	140 - 170°C
Evaporation Rate (ether = 1)	40
Pour Point	< -100°C
pH	Neutral low
Solubility In Water	Low
Kauri-Butanol Value	> 200

MATERIALS COMPATIBILITY

OK	Non-corrosive to metals
CAUTION	May be harmful to some plastics and will soften some paints
NOT OK	-

STORAGE & SHELF LIFE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 6 years with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

HEALTH AND SAFETY

A separate Safety Data Sheet (SDS) according to EC Regulation 73/404/EEC and 648/2004/EC is available from Ambersil.com or via info.uk@crcind.com

MISREPRESENTATION ACT 1967

TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

Version 2.0
Created: July 2019
Updated: N/A

CRC Industries UK Ltd.
Wylds Road, Bridgwater
Somerset, TA6 4DD
United Kingdom

t +44 (0)1278 727200
f +44 (0)1278 425644
e sales.uk@crcind.com
w www.ambersil.com

Company Registered No. 04910479

VAT No. GB 821 5195 42

