



## BELT DRESSING FG

### FOOD PROCESSING SAFE® ADHESIVE BELT LUBRICANT

A clear liquid formulated specially for use on all types of belts found in food manufacturing equipment to increase pulling power, prevent belt slippage due to heat, cold, dampness or dust, and eliminate belt squeak, where incidental food contact may occur.

Works on all type of belt - vee, flat, toothed, rubber, leather, and fabric. Keeps belts 'soft' and glaze free, and protects belts from deterioration through oxidation and heat.



Lubricants



360° Spray System for all angle use



NSF Registered: category H1, no 140257



Just one of over 25 FG products



Prevention. Not Detection. Locked in for safety

### PRODUCT CODES / FILL SIZES



30257 / 400ml

### APPLICATIONS

Eliminates slippage in flat, round or V-belts made out of rubber, leather, fabrics, plastic etc, used on:

- Compressors, pumps, generators
- Fans, motors, lift trucks
- Conveyors, industrial machinery

### DIRECTIONS

- Turn off equipment and stop belts before applying
- Spray a light, even coating on pulling sides of belt (i.e. sides that come in contact with pulleys);
- Let solvent evaporate before re-energising equipment
- Re-apply occasionally to ensure continued high performance
- Remove, if necessary, with Amberklene FG or Industrial Degreaser FG (test compatibility with rubber and plastic prior to use)

## TECHNICAL DATA (WITHOUT PROPELLANT)

Appearance	Clear Liquid
Specific Gravity (@ 20°C)	0.75
Flash Point (closed cup)	< 0°C
Specific Gravity (@ 20°C)	0.91
Max. temp. (continuous)	100°C
Viscosity (@ 99°C)	4100 mPa.s
Average mol. Wt	2300
Based upon the present state of our knowledge and information received from our suppliers, evaluation of this product indicates that it is free from nut oils and their derivatives.	

## MATERIALS COMPATIBILITY

OK	-
CAUTION	-
NOT OK	-

## STORAGE & SHELF LIFE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 6 years with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

## HEALTH AND SAFETY

A separate Safety Data Sheet (SDS) according to EC Regulation 73/404/EEC and 648/2004/EC is available from Ambersil.com or via [info.uk@crcind.com](mailto:info.uk@crcind.com)

## MISREPRESENTATION ACT 1967

## TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

Version 2.0  
Created: July 2019  
Updated: N/A

CRC Industries UK Ltd.  
Wylds Road, Bridgwater  
Somerset, TA6 4DD  
United Kingdom

t +44 (0)1278 727200  
f +44 (0)1278 425644  
e [sales.uk@crcind.com](mailto:sales.uk@crcind.com)  
w [www.ambersil.com](http://www.ambersil.com)

Company Registered No. 04910479

VAT No. GB 821 5195 42

