



Safety Data Sheet according to (EC) No 1907/2006

Page 1 of 9

Loctite 7649

sds no. : 179515
V002.3

Revision: 05.01.2011
printing date: 08.06.2011

1. Identification of the substance/mixture and of the company/undertaking

Product identifier:

Loctite 7649

Relevant identified uses of the substance or mixture and uses advised against:

Intended use:
activator

Details of the supplier of the safety data sheet:

Henkel Ireland Limited
Product Safety & Regulatory Affairs
Tallaght Business Park, Whitestown
Dublin 24

Ireland

Phone: +353 (14046444)
Fax-no.: +353 (14519926)

ua-productsafety.uk@uk.henkel.com

Emergency telephone number:

24 Hours Emergency Tel: +44 (0)1442 278497

2. Hazards identification

Classification of the substance or mixture:

Classification (DPD):

F+ - Extremely flammable
R12 Extremely flammable.
Xi - Irritant
R36 Irritating to eyes.
R66 Repeated exposure may cause skin dryness or cracking.
R67 Vapours may cause drowsiness and dizziness.

Label elements (DPD):

Xi - Irritant

F+ - Extremely flammable

**Risk phrases:**

- R12 Extremely flammable.
- R36 Irritating to eyes.
- R66 Repeated exposure may cause skin dryness or cracking.
- R67 Vapours may cause drowsiness and dizziness.

Safety phrases:

- S23 Do not breathe vapour.
- S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- S37 Wear suitable gloves.
- S51 Use only in well-ventilated areas.

Additional labeling:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.

Keep out of the reach of children

For consumer use only: S2 Keep out of the reach of children

S46 If swallowed, seek medical advice immediately and show this container or label.

Other hazards:

The aerosol container is under pressure. Do not expose to high temperatures.

3. Composition/information on ingredients**General chemical description:**

Activator

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Acetone 67-64-1	200-662-2	80- 100 %	Flammable liquids 2 H225 Specific target organ toxicity - single exposure 3 H336 Serious eye irritation 2 H319
Propane 74-98-6	200-827-9	10- 20 %	Flammable gases 1 H220 Gases under pressure

Only dangerous ingredients for which a CLP classification is already available are displayed in this table.

For full text of the H - statements and other abbreviations see section 16 "Other information".

Substances without classification may have community workplace exposure limits available.

Declaration of ingredients according to DPD (EC) No 1999/45:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Acetone 67-64-1	200-662-2	80 - 100 %	R66 Xi - Irritant; R36 F - Highly flammable; R11 R67
Propane 74-98-6	200-827-9	10 - 20 %	F+ - Extremely flammable; R12

For full text of the R-Phrases indicated by codes see section 16 'Other Information'.
Substances without classification may have community workplace exposure limits available.

4. First aid measures**Description of first aid measures:****Inhalation:**

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.
Seek medical advice.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

Ingestion:

Rinse out mouth, drink 1-2 glasses of water, do not induce vomiting.
Seek medical advice.

Most important symptoms and effects, both acute and delayed:

Vapors may cause drowsiness and dizziness.

Indication of any immediate medical attention and special treatment needed:

See section: Description of first aid measures

5. Firefighting measures**Extinguishing media:****Suitable extinguishing media:**

Carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

None known

Special hazards arising from the substance or mixture:

None
Oxides of carbon, oxides of nitrogen, irritating organic vapors.

Advice for firefighters:

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Avoid skin and eye contact.
Ensure adequate ventilation.
See advice in chapter 8

Environmental precautions:

Do not let product enter drains.

Methods and material for containment and cleaning up:

For small spills wipe up with paper towel and place in container for disposal.
For large spills absorb onto inert absorbent material and place in sealed container for disposal.
Dispose of contaminated material as waste according to Chapter 13.

7. Handling and storage

Precautions for safe handling:

Use only in well-ventilated areas.
Vapours should be extracted to avoid inhalation.
Keep away from sources of ignition - no smoking.

Hygiene measures:

Wash hands before work breaks and after finishing work.
Do not eat, drink or smoke while working.
Good industrial hygiene practices should be observed.

Conditions for safe storage, including any incompatibilities:

Store in a cool, well-ventilated place.
Keep away from heat and direct sunlight.

Specific end use(s):

activator

8. Exposure controls/personal protection

Control parameters:

Valid for
Great Britain
Basis
UK EH40 WELs

Ingredient	ppm	mg/m3	Type	Category	Remarks
ACETONE 67-64-1	1.500	3.620	Short Term Exposure Limit (STEL):		EH40 WEL
ACETONE 67-64-1	500	1.210	Time Weighted Average (TWA):		EH40 WEL
ACETONE 67-64-1	500	1.210	Time Weighted Average (TWA):	Indicative	ECTLV
PROPANE 74-98-6				Included in the regulation but with no data values. See regulation for further details	EH40 WEL

Exposure controls:**Respiratory protection:**

Use only in well-ventilated areas.
Filter type: P2

Hand protection:

The use of chemical resistant gloves such as Neoprene or Natural Rubber are recommended
Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:
Wear protective glasses.

Skin protection:
Wear suitable protective clothing.

9. Physical and chemical properties

Information on basic physical and chemical properties:

Appearance	aerosol
	Green
Odor	Pungent
pH	not applicable
Initial boiling point	56 °C (132.8 °F)
Flash point	-18 °C (0.4 °F)
Decomposition temperature	No data available / Not applicable
Vapour pressure	230 mbar
(20 °C (68 °F))	
Density	0,8 g/cm ³
(20 °C (68 °F))	
Bulk density	No data available / Not applicable
Viscosity	No data available / Not applicable
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Solubility (qualitative)	Miscible
(Solvent: Water)	
Solubility (qualitative)	Soluble
(Solvent: Acetone)	
Solidification temperature	No data available / Not applicable
Melting point	No data available / Not applicable
Flammability	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Explosive limits	
lower	2,5 % (V)
upper	13 % (V)
Partition coefficient: n-octanol/water	No data available / Not applicable
Evaporation rate	No data available / Not applicable
Vapor density	No data available / Not applicable
Oxidising properties	No data available / Not applicable

Other information:

No data available / Not applicable

10. Stability and reactivity

Reactivity:

Reacts with strong oxidants.

Chemical stability:

Stable under recommended storage conditions.

Possibility of hazardous reactions:

See section reactivity

Conditions to avoid:

Stable

Incompatible materials:

No data available.

Hazardous decomposition products:

Irritating organic vapours.

11. Toxicological information

General toxicological information:

The preparation is classified based on the conventional method outlined in Article 6(1)(a) of Directive 1999/45/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

Oral toxicity:

This material is considered to have low toxicity if swallowed.

Inhalative toxicity:

May cause headache and dizziness.

Skin irritation:

Solvent may remove essential oils from the skin making it susceptible to attack from other chemicals.

Eye irritation:

Irritating to eyes.

Acute toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Acetone 67-64-1	LD50 LC50 LD50	5.800 mg/kg 76 mg/l > 15.688 mg/kg	oral inhalation dermal	4 h	rat rat rabbit	

Serious eye damage/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Acetone 67-64-1	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Acetone 67-64-1	negative	bacterial forward mutation assay	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)

Repeated dose toxicity

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
Acetone 67-64-1	NOAEL=2500 ppm	oral: drinking water	13 weeks	rat	

12. Ecological information

General ecological information:

The preparation is classified based on the conventional method outlined in Article 6(1)(a) of Directive 1999/45/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

Ecotoxicity:

Do not empty into drains / surface water / ground water.

Mobility:

The product evaporates readily.

Persistence and Biodegradability:

No data available.

Bioaccumulative potential:

No data available.

Toxicity:

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
Acetone 67-64-1	LC50	8.120 mg/l	Fish	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
Acetone 67-64-1	EC50	6.098,4 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Persistence and degradability:

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
Acetone 67-64-1	readily biodegradable	aerobic	81 - 92 %	EU Method C.4-E (Determination of the "Ready" BiodegradabilityClosed Bottle Test)

Bioaccumulative potential / Mobility in soil:

Hazardous components CAS-No.	LogKow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
Acetone 67-64-1	0,24					

13. Disposal considerations**Waste treatment methods:**

Product disposal:

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

Disposal must be made according to official regulations.

Waste code

14 06 03 Other solvents and solvent mixtures

14. Transport information**Road transport ADR:**

Class: 2
Packaging group:
Classification code: 5F
Hazard ident. number:
UN no.: 1950
Label: 2.1
Technical name: AEROSOLS
Tunnelcode: (D)

Railroad transport RID:

Class:	2
Packaging group:	
Classification code:	5F
Hazard ident. number:	23
UN no.:	1950
Label:	2.1
Technical name:	AEROSOLS
Tunnelcode:	

Inland water transport ADN:

Class:	2
Packaging group:	
Classification code:	5F
Hazard ident. number:	
UN no.:	1950
Label:	2.1
Technical name:	AEROSOLS

Marine transport IMDG:

Class:	2.1
Packaging group:	
UN no.:	1950
Label:	2.1
EmS:	F-D ,S-U
Seawater pollutant:	-
Proper shipping name:	AEROSOLS

Air transport IATA:

Class:	2.1
Packaging group:	
Packaging instructions (passenger)	203
Packaging instructions (cargo)	203
UN no.:	1950
Label:	2.1
Proper shipping name:	Aerosols, flammable

15. Regulatory information**Safety, health and environmental regulations/legislation specific for the substance or mixture:**

VOC content (1999/13/EC)	99 %
-----------------------------	------

16. Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

- R11 Highly flammable.
- R12 Extremely flammable.
- R36 Irritating to eyes.
- R66 Repeated exposure may cause skin dryness or cracking.
- R67 Vapours may cause drowsiness and dizziness.
- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

This safety data sheet was prepared in accordance with Council Directive 67/548/EEC and its subsequent amendments, and Commission Directive 1999/45/EC.