

Description

An effective absorbent sheet for use in the event of spills involving water or oil based products, and acids or alkalis, suitable for use in most industrial applications. Being light and easy to handle they are easily deployed in quantities relevant to the spill size, therefore avoiding the waste associated with granular absorbents. They can easily be disposed of once saturated and are useful when used around leaking machinery.

Benefits & Features

- Light and easy to deploy
- Cost effective
- Melt blown for maximum absorption
- Absorbs without leaving messy deposits
- Absorbs both oil and water based spills
- Resistant to acids and alkalis
- Durable and resilient outer covering
- Leaves the floor drier
- Low linting
- Dimpled for better cohesion and strength
- Perforated for economic use

Directions for Use

Suitable protective equipment should be worn. Lay sheets sufficient to cover the spill. Leave until saturated and dispose of in line with local and national regulations.

Technical Data

Appearance:	Yellow fibrous sheet
Material:	Melt blown polypropylene
Dimensions:	50 x 40cm
Density:	260g/m ²
Absorbency:	Approx 1 litre per sheet depending on product to be absorbed
Saturation Time:	Approx 60-90 seconds for 10W/40 engine oil

Packaging

1 Pack = 100 Mats



Note

This technical data sheet is for general guidance purposes only and may contain information that is inappropriate for certain conditions of use. Accordingly, all recommendations and suggestions are made without guarantee. Further information is available from our Technical Department.