

Description

General purpose absorbent roll. A melt blown perforated and dimpled roll used for quick deployment in the event of an oil or water based spill and as a walkway protector. With dimpling for extra strength and low linting properties these rolls are an effective method of keeping work areas clean. Perforated two ways, they can be torn where required for economic usage and to fit around machinery. In the event of a large spill this would be used as an early measure, being rolled out quickly for absorption of large amounts of fluid.

Benefits & Features

- Quickly rolled out for fast response
- Melt blown for high absorption rates
- Dimpled for cohesion and strength
- Perforated for economic use
- Use for catching overspray
- Prevents transfer of soiling to clean areas
- Use for oil or water based spills

Directions for Use

Suitable protective equipment should be worn. Roll out across a large spill, working in a criss cross fashion for maximum absorption. Use as a walkway protector by rolling out to desired size, tearing off at perforations to fit around obstacles.

Technical Data

Appearance:	Grey perforated and dimpled roll
Material:	Polypropylene
Dimensions:	96cm wide x 45 metres long
Density:	260g/m ²
Absorbency:	Approx 210 litres per roll depending on product to be absorbed
Saturation Time:	Approx 60-90 seconds for 10W/40 engine oil

Packaging

1 Pack = 1 Roll

Note

This technical data sheet is for general guidance purposes only and may contain information that is inappropriate for certain conditions of use. Accordingly, all recommendations and suggestions are made without guarantee. Further information is available from our Technical Department.

