

## Description

Oil Only absorbent sheets. An effective absorbent sheet for use in the event of spills involving oil based products, suitable for use in most industrial applications. Being light and easy to handle they are easily deployed in quantities relevant to the spill size, therefore avoiding the waste associated with granular absorbents. They can easily be disposed of once saturated and are useful when used around leaking machinery.

## Benefits & Features

- Light and easy to deploy
- Cost effective
- Melt blown for maximum absorption
- Absorb without leaving messy deposits
- Absorb oil based spills
- Perforated for economical use
- Dimpled for extra strength
- Leave the floor dry
- Water repellent – good for use outside or on water

## Directions for Use

Suitable protective equipment should be worn. Lay sheets sufficient to cover the spill. Leave until saturated and dispose of in line with local and national regulations.

## Technical Data

Appearance:	White perforated and dimpled fibrous sheet
Material:	Melt blown polypropylene
Dimensions:	50 x 40cm
Density:	170g/m <sup>2</sup>
Absorbency:	Approx 0.65 litres per sheet depending on product to be absorbed
Saturation Time:	Approx 20-30 seconds for 10W/40 engine oil

## Packaging

1 Pack = 200 Mats

## Note

This technical data sheet is for general guidance purposes only and may contain information that is inappropriate for certain conditions of use. Accordingly, all recommendations and suggestions are made without guarantee. Further information is available from our Technical Department.

