



ALUMINIUM ANTI SEIZE & ASSEMBLY PASTE ALU-TECH

Product Overview

Alu-Tech is specially formulated, high temperature, anti-seize thread and flange lubricant, which will prevent seizure and damage on all threaded and mating surface connections at high temperatures and in corrosive conditions.

Typical Applications

- **Pipe flanges, valves, brake adjusters, manifolds, press pivots, punch nose, Hot gas valves and coking plant.**
- **Die fixing and tie bars.**
- **Cranes, winches, etc.**

Features and Benefits

- Prevents corrosion and seizure in high humidity and marine environments on all threaded connections
- Prevents pick up and galling on assembly
- Aids disassembly, even after long periods.
- High temperature protection up to 1200°
- Will not run out at high temperatures
- Provides a virtually indestructible film, even in the most severe conditions.
- Also available in 400ml aerosol

Directions for Storage and Use

Product is to be stored in a clean, dry, storage area in its original sealed packaging.

Shelf Life (unopened) – 3 years approx *

*Some bleeding may occur, thorough mixing will homogenise the mixture to its original state.

Apply to male and female component parts before assembly.

Disclaimer

The data sheet is based on personal knowledge and experience and is given as a guideline to its possible uses. It does not take into account variables or conditions out of our control that can affect our product in any way. It is the users' sole responsibility to ensure that the product is suitable for the purpose for which it is being used and this data does not in any way form a warranty. If you are unsure of its suitability please contact us and we will be happy to discuss your needs and supply a sample for testing if required. New Tech Lubes Ltd is committed to supplying the best products and may therefore change the information in this specification at any time.

Available Sizes
100ml Lube Tube
500g Pot
12.5kg Pail
Also available in
400ml Aerosol

Available Grades
NLGI 2

Physical Characteristics	
Temperature Range	Up To 1200°C
Colour	Silver
Load Capacity	4700 Bar
Flashpoint (Base Only)	>200°C
Carrier	Non Melting Grease

Safety Data Sheets

Safety data sheets are available for download from our website, scan the QR code to take you to our website



www.newtechlubes.com

**New
Tech
Lubes
Limited**

Unit 3 & 4
Harrison Drive Ind Est
Worksop, Nottinghamshire
UK, S81 9RL

t. 01909 730900
f. 01909 730909
e. info@newtechlubes.com
w. www.newtechlubes.com

