



FOOD SAFE SYNTHETIC AIRLINE OIL FS AIRLINE

Product Overview

FS Airline is a low viscosity lubricant ideally suited to the lubrication of airlines and airtools in sensitive areas such as food and beverage production or pharmaceutical sites. Due to its high performance, FS Airline can be used for airline lubrication in all industries

Features and Benefits

- FS Airline is hydrophobic removing the risk of emulsification allowing water to be easily drained from the systems.
- Extend the life of tools through proper lubrication and protection from water and corrosion.
- H1 Registered to comply with food safe requirements and auditors standards.
- Excellent cold weather performance for all year use.
- Odourless, tasteless and water white making it clean in use.
- InS H1 Registered, made with FDA listed ingredients

Typical Applications

- **Airlines**
- **Air Tools**
- **Light lubricant for any other mechanisms**
- **General purpose , food grade lubricant for lightly loaded chains, slideways etc**

Directions for Storage and Use

Product is to be stored in a clean, dry, storage area in its original sealed packaging.

Shelf Life (unopened) – 3 years approx

Disclaimer

The data sheet is based on personal knowledge and experience and is given as a guideline to its possible uses. It does not take into account variables or conditions out of our control that can affect our product in any way. It is the users' sole responsibility to ensure that the product is suitable for the purpose for which it is being used and this data does not in any way form a warranty. If you are unsure of its suitability please contact us and we will be happy to discuss your needs and supply a sample for testing if required. New Tech Lubes Ltd is committed to supplying the best products and may therefore change the information in this specification at any time.

Available Sizes
250ml Oil Spout Bottle
5ltr
25ltr

Available Grades

Physical Characteristics	
Specific Gravity	0.85
Operating Temp	-60°C to 240°C
Flash Point	246°C
Pour Point	-63°C
Salt Spray	Pass
Viscosity	31.6
Water Resistance	100%
Ash content %	Nil

Safety Data Sheets

Safety data sheets are available for download from our website, scan the QR code to take you to our website



www.newtechlubes.com

**New
Tech
Lubes
Limited**

Unit 3 & 4
Harrison Drive Ind Est
Worksop, Nottinghamshire
UK, S81 9RL

t. 01909 730900
f. 01909 730909
e. info@newtechlubes.com
w. www.newtechlubes.com

