



## FOOD SAFE ANTI SEIZE & ASSEMBLY PASTE

# FS ANTI SEIZE

### Product Overview

*FS Anti-Seize is a white, anti seize, compound formulated for use on assemblies in difficult areas where fretting corrosion and corrosion induced by wet environments may occur. It is suitable for use in food, beverage, pharmaceutical and clean environments as it is INS H1 Registered*

### Features and Benefits

- Non - Toxic
- Suitable for use on stainless steel
- Highly water resistant
- Long Lasting formulation
- Contains PTFE as well as other boundary lubricants
- InS H1 Registered, made with FDA listed Ingredients
- Safety Data

### Typical Applications

- **Threaded components**
- **Bushes**
- **Slides**
- **Food, Beverage, pharmaceutical and all other clean environments**

### Directions for Storage and Use

Product is to be stored in a clean, dry, storage area in its original sealed packaging.

Shelf Life (unopened) – 3 years approx \*

\*Some bleeding may occur, thorough mixing will homogenise the mixture to its original state.

Product can be applied by brush or applicator

Apply to clean, dry parts only.

#### Disclaimer

The data sheet is based on personal knowledge and experience and is given as a guideline to its possible uses. It does not take into account variables or conditions out of our control that can affect our product in any way. It is the users' sole responsibility to ensure that the product is suitable for the purpose for which it is being used and this data does not in any way form a warranty. If you are unsure of its suitability please contact us and we will be happy to discuss your needs and supply a sample for testing if required. New Tech Lubes Ltd is committed to supplying the best products and may therefore change the information in this specification at any time.

Available Sizes
100g Lube Tube
500gm Tub
1Kg Tub
5kg Pail

Available Grades
NLGI 2/3

Physical Characteristics	
Appearance	White
Weld Load	540kg
Thickener	Aluminium soap
Water Resistance after 500 hours	100%
Evaporation less ASTM D-972	< 1%
Temperature Range	-32°C - 350°C
Grade	NLGI 2/3

### Safety Data Sheets

Safety data sheets are available for download from our website, scan the QR code to take you to our website



[www.newtechlubes.com](http://www.newtechlubes.com)

**New  
Tech  
Lubes  
Limited**

Unit 3 & 4  
Harrison Drive Ind Est  
Worksop, Nottinghamshire  
UK, S81 9RL



t. 01909 730900  
f. 01909 730909  
e. [info@newtechlubes.com](mailto:info@newtechlubes.com)  
w. [www.newtechlubes.com](http://www.newtechlubes.com)

