



FOOD SAFE SYNTHETIC COMPRESSOR OIL FS COMP TECH 68

Product Overview

FS Comp Tech is a range of synthetic, compressor oils with high performance additives to provide a clean, long lasting lubricant.

It is suitable for use in food, beverage, pharmaceutical and clean environments as it is NSF H1 Registered

FS Comp Tech is also suitable for use in Vacuum Pumps

Typical Applications

- **Compressors**
- **Hydraulic systems**
- **Vacuum Pumps**
- **Lubrication of sliding surfaces and pivots**
- **Airline lubricant**
- **Lightly loaded chains**

Features and Benefits

- Low friction coefficient reduces wear and energy consumption.
- Fully synthetic oil allows extended service intervals.
- Very wide temperature range.
- Low foaming formulation.
- Greatly reduces residue, varnish and scum build up so reducing maintenance costs.
- NSF H1 Registered, made with FDA listed ingredients

Directions for Storage and Use

Product is to be stored in a clean, dry, storage area in its original sealed packaging.

Shelf Life (unopened) – 3 years approx *

Do not mix with other lubricants if compatibility is not known, for best results purge system of other lubricants. Apply to clean, dry parts only.



Nonfood Compounds
H1 161702



Disclaimer

The data sheet is based on personal knowledge and experience and is given as a guideline to its possible uses. It does not take into account variables or conditions out of our control that can affect our product in any way. It is the users' sole responsibility to ensure that the product is suitable for the purpose for which it is being used and this data does not in any way form a warranty. If you are unsure of its suitability please contact us and we will be happy to discuss your needs and supply a sample for testing if required. New Tech Lubes Ltd is committed to supplying the best products and may therefore change the information in this specification at any time.

Available Sizes
5ltr
20Ltr
205ltr

Available Grades
ISO 46 - 68 - 100

Physical Characteristics	
Appearance	Clear Fluid
Base Fluid	Polyalphaolefin
Viscosity	ISO 68
Temperature range	-30°C to +150°C

Safety Data Sheets

Safety data sheets are available for download from our website, scan the QR code to take you to our website



www.newtechlubes.com

**New
Tech
Lubes
Limited**

Unit 3 & 4
Harrison Drive Ind Est
Worksop, Nottinghamshire
UK, S81 9RL

t. 01909 730900
f. 01909 730909
e. info@newtechlubes.com
w. www.newtechlubes.com

