



FOOD SAFE DISMANTLING FLUID FS EASE

Product Overview

FS Ease is a semi-synthetic water clear, odourless, tasteless and food safe lubricant. Designed to penetrate and aid in the dismantling of difficult components and fasteners.

FS-Ease contains hydrophobic oil making it perfect for use in wet areas, dispersing water lubricating and protecting metal surfaces from corrosion.

Features and Benefits

- Clean in use. Water clear, tasteless, odorless fluid.
- Disperses water, loosens dirt and grease on soiled surfaces.
- Contains hydrophobic oil to lubricate and leave water resistant coating
- Protects against corrosion.
- Versatile
- InS H1 registered made with FDA listed ingredients

Also available as a 400ml aerosol can for fast, easy and precise application

Typical Applications

- **Penetrate seized components**
- **Clean components and surfaces.**
- **De-watering**
- **Lubricate delicate mechanisms, slides and pivots**
- **It is suitable for use in food, beverage, pharmaceutical and clean environments as it is INS H1 Registered**

Directions for Storage and Use

Product is to be stored in a clean, dry, storage area in its original sealed packaging.

Shelf Life (unopened) – 3 years approx *

Disclaimer

The data sheet is based on personal knowledge and experience and is given as a guideline to its possible uses. It does not take into account variables or conditions out of our control that can affect our product in any way. It is the users' sole responsibility to ensure that the product is suitable for the purpose for which it is being used and this data does not in any way form a warranty. If you are unsure of its suitability please contact us and we will be happy to discuss your needs and supply a sample for testing if required. New Tech Lubes Ltd is committed to supplying the best products and may therefore change the information in this specification at any time.

Available Sizes
5Ltr
25ltr
400ml Aerosol

Available Grades
N/A

Physical Characteristics	
Odour	None
Colour	Water white
Flash point (°C)	>30°C
Flash Point aerosol propellant (°C)	0°C
Viscosity @ 25oC ASTM D445	1.09 mm2/s
Pour Point (°C)	-62°C

Safety Data Sheets

Safety data sheets are available for download from our website, scan the QR code to take you to our website



www.newtechlubes.com

**New
Tech
Lubes
Limited**

Unit 3 & 4
Harrison Drive Ind Est
Worksop, Nottinghamshire
UK, S81 9RL

t. 01909 730900
f. 01909 730909
e. info@newtechlubes.com
w. www.newtechlubes.com

