New Tech Lubes Limited

Technical Data Sheet NTL TDS 1007A-1.0





ANTI FLING CHAIN LUBE HI TACK CHAIN OIL AEROSOL

Product Overview

Hi Tack Chain Oil is a general purpose lubricating oil containing effective anti fling agents and a combination of EP additives.

Features and Benefits

- Reduce fling off associated with standard chain oils
- Provide exceptional Anti Wear and Anti Friction properties.
- Penetrate deep into links and pins for maximum effect.
- High viscosity base oil to improve shock loading ability.
- Protects chains from corrosion

Typical Applications

- **Conveyors**
- **Fork lifts**
- **Drive chains**
- **Bikes**
- **Open Chains**

Directions for Storage and Use

Spray onto parts to be coated and allow solvents to evaporate and oil to form before use.

Product is to be stored in a clean, dry, storage area in its original sealed

Shake can well before use.

Caution: Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not puncture or incinerate even when empty. Do not spray on any naked flame or any incandescent material

The data sheet is based on personal knowledge and experience and is given as a guideline to its possible uses. It does not take into account variables or conditions out of our control that can affect our product in any way. It is the users' sole responsibility to ensure that the product is suitable for the purpose for which it is being used and this data does not in any way form a warranty. If you are unsure of its suitability please contact us and we will be happy to discuss your needs and supply a sample for testing if required. New Tech Lubes Ltd is committed to supplying the best products and may therefore change the information in this specification at

Available Sizes		
500ml Aerosol		

Physical Characteristics	
Flashpoint	>110°C (Aerosol Propellant<0°C)
Constituents	HBP fractions + additives
Appearance	Brown Fluid
Base Oil Viscosity	460cst
Operating Temp Range	-10°C to 120°C

Available Grades

Safety Data Sheets

Safety data sheets are available for download from our website, scan the QR code to take vou to our website

www.newtechlubes.com



New Tech Lubes Limited

Unit 3 & 4 Harrison Drive Ind Est Worksop, Nottinghamshire e. info@newtechlubes.com UK, S81 9RL

t. 01909 730900

f. 01909 730909

w. www.newtechlubes.com

