



NON MELTING GREASE WITH GRAPHITE HI TEMP



Product Overview

Hi Temp is a high temperature, non-melting, general-purpose lubricant containing Graphite. This gives this grease outstanding load carrying and lubrication capabilities.

Features and Benefits

- Replaces several greases
- Reduce wear
- Operating temperature -10°C to 190°C
- Graphite to protect at elevated temperatures
- Non-melting - will not run or drip
- Extend service intervals
- Safety Data

Typical Applications

Recommended for manual or automatic application to all bearings operating in aggressive environments.

- Plain Bearing
- Anti-Friction Bearings
- Fifth Wheel Couplings
- Universal joints
- Pumps
- Steering Joints

Directions for Storage and Use

Product is to be stored in a clean, dry, storage area in its original sealed packaging.

*Shelf Life (unopened) – 3 years approx **

**Some bleeding may occur, thorough mixing will homogenise the mixture to its original state.*

Product can be applied by brush, applicator or automatic lubrication system.

Do not mix with other lubricants if compatibility is not known, for best results purge system of other lubricants. Apply to clean, dry parts only.

Disclaimer

The data sheet is based on personal knowledge and experience and is given as a guideline to its possible uses. It does not take into account variables or conditions out of our control that can affect our product in any way. It is the users' sole responsibility to ensure that the product is suitable for the purpose for which it is being used and this data does not in any way form a warranty. If you are unsure of its suitability please contact us and we will be happy to discuss your needs and supply a sample for testing if required. New Tech Lubes Ltd is committed to supplying the best products and may therefore change the information in this specification at any time.

Available Sizes
400g Cartridge
5Kg Tub
12.5 Kg Pail
25 Kg Pail
50 Kg Pail
180 Kg Barrel

Available Grades
NLGI 2

Physical Characteristics	
Temperature Range	-10°C to 190°C (250°C for short periods)
Penetration (worked)	265 - 295 (N.L.G.I. No. 2)
Drop Point	Infusible
Flashpoint	>200°C

Safety Data Sheets

Safety data sheets are available for download from our website, scan the QR code to take you to our website



www.newtechlubes.com