
View product details on medias

22.10.2026, 14:31:07 BST

SCHAEFFLER




KTHK40-B-PP-AS

Linear Ball Bearing and Housing Unit


Linear ball bearing and housing unit; sealed, greased, with relubrication facility; corrosion-resistant design possible

Technical information



Your current product variant


Size code	40
Version	B
Sealing	PP
Relubrication feature	AS



Main Dimensions & Performance Data

F_W	40 mm	Diameter of ball complement
H	73.5 mm	Height
L	125 mm	Length
B	87 mm	Width
C	8,600 N	Load capacity dyn. C
C_0	6,900 N	Load capacity stat. C0
≈m	1.6 kg	Weight

The data sheet only contains an overview of the technical data of the selected product. Please refer to the additional documentation for this product. For further information, please use the following link on our website



Mounting dimensions

J_B	69 mm	
Tol J_B	+ 0.15 mm	Upper tolerance
Tol J_B	- 0.15 mm	Lower tolerance
B_1	63 mm	
A_5	43.5 mm	
J_L	85 mm	Distance
Tol J_L	+ 0.15 mm	Upper tolerance
Tol J_L	- 0.15 mm	Lower tolerance
H_2	39 mm	Center height
Tol H_2	+ 0.01 mm	Upper tolerance
Tol H_2	- 0.014 mm	Lower tolerance
H_4	49.7 mm	
H_5	12.8 mm	
T_5	22 mm	
H_6	38 mm	
A_3	23 mm	
G_2	M10	
N_1	8.4 mm	
N_3	18 mm	
K_5	M8	
K_8	NIPA2	Lubrication nipple

The data sheet only contains an overview of the technical data of the selected product. Please refer to the additional documentation for this product. For further information, please use the following link on our website