



SIZE BSPP (E)	PRODUCT CODE	PRESSURE (BAR)	A	B	C	D	F A/F	G A/F	KG EACH
1/8	MBH02P	350	38	8.1	28.1	3.5	14.3	15.9	0.030
1/4	MBH04P	350	47	11.1	28.1	5.1	19.1	19.1	0.055
3/8	MBH06P	350	52	12.1	32.1	8.1	22.2	22.2	0.085
1/2	MBH08P	315	60	14.1	35.1	11.1	28.6	28.6	0.15
3/4	MBH12P	250	66	16.1	38.1	16.7	31.7	35.1	0.21
1	MBH16P	200	74	19.1	41.1	22.2	41.3	44.4	0.35
1-1/4	MBH20P	160	81	20.1	44.1	28.7	50.8	50.8	0.55
1-1/2	MBH24P	125	88	22.1	48.1	33.3	56.4	63.5	0.78
2	MBH32P	80	95	25.1	48.1	46.0	69.8	69.8	1.04

**** DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL ****

NERO's range of Male Bulkhead fittings are available in BSPP thread form with a 60° internal cone on the male ends & recessed to accept a Bonded Washer

Pressure rating up to 350 BAR (size dependant)

Can be supplied with 2.2 Certificate of Conformity - upon request

BSPP Male threads are to ISO 228/1
60° internal cone to BS 5200

We stock a wide range of Hydraulic Fittings to suit your requirements



We also keep a Female version of this fitting + Bonded Washers in our Hydraulic range

