



NICKEL ANTI SEIZE PASTE NICKEL TECH

Product Overview

Nickel Tech is an anti seize paste for protecting joining components and threaded fasteners from seizure and corrosion.

Nickel-Tech is very effective at preventing surface to surface contact even at extremely elevated temperatures and is ideal for when copper cannot be present.

Features and Benefits

- Free from copper
- Will not poison catalyst beds.
- Compatible with Stainless steel and nickel alloys.
- Excellent resistance to Acids, Chemical corrosion and oxidation.
- Excellent resistance to caustic and environments of ammonia or ammonium compounds.
- Wide operating range -55°C to 1400°C.
- High load ability

Typical Applications

**Nickel Tech is recommended for use where metal to metal contact needs to be minimized on threaded connections, bushes, pins, hinges, keys and keyways.
Compatible with all metals including stainless steel and nickel alloys.**

Directions for Storage and Use

Product is to be stored in a clean, dry, storage area in its original sealed packaging.

Shelf Life (unopened) – 3 years approx*

*Some bleeding may occur, thorough mixing will homogenise the mixture to its original state.

Product can be applied by brush or applicator.

Do not mix with other lubricants if compatibility is not known, for best results purge system of other lubricants. Apply to clean, dry parts only

Disclaimer

The data sheet is based on personal knowledge and experience and is given as a guideline to its possible uses. It does not take into account variables or conditions out of our control that can affect our product in any way. It is the users' sole responsibility to ensure that the product is suitable for the purpose for which it is being used and this data does not in any way form a warranty. If you are unsure of its suitability please contact us and we will be happy to discuss your needs and supply a sample for testing if required. New Tech Lubes Ltd is committed to supplying the best products and may therefore change the information in this specification at any time.

Available Sizes
100gm Tube
500gm Pot
400ml Cart
5kg Tub

Available Grades

Physical Characteristics	
Appearance	Smooth Paste
Colour	Silver/Grey
Grade	NLGI 2
Worked Penetration (mm)	265 to 295
Temperature Range (°C)	-55 to 1400
Solids Content	20%

Safety Data Sheets

Safety data sheets are available for download from our website, scan the QR code to take you to our website



www.newtechlubes.com