



Unit 3 & 4
Harrison Drive Ind Est
Worksop, Nottinghamshire
UK, S81 9RL

t. 01909 730900
f. 01909 730909
e. info@newtechlubes.com
w. www.newtechlubes.com

🐦 @newtechlubes.com

OPEN GEAR & ROPE GREASE

SECTION 1. IDENTIFICATION OF THE PREPARATION AND THE COMPANY / UNDERTAKING

- 1.1 Product Name:** Open Gear and Rope Spray (Aerosol)
1.2 Identified uses: Lubricant.
1.3 Details of supplier of sds: New Tech Lubes Ltd, Unit 3 Harrison Drive Ind Est, Worksop Notts, S81 9RL
E Mail (competent person) info@newtechlubes.com
1.4 Emergency Telephone: +44 (0)1909 730900 (09.00 -17.00 GMT Monday to Friday)

SECTION 2. HAZARDS IDENTIFICATION

2.1 Classification of the substance /mixture:

2.1.1 Regulation EC 1272/2008:

Aerosol (cat 1)	H222
Health - Skin irritation (cat 2)	H315
(STOT SE3)	H336,
Enviro - Aquatic chronic (cat 3)	H412.

2.2 Label elements:

Contains: Paraffinic hydrocarbons



Signal word(s): Danger

Hazard statements:

H222	Extremely flammable aerosol
H229	Pressurised container: may burst if heated
H315	Causes skin irritation
H336	May cause drowsiness or dizziness.
H412.	Harmful to aquatic life with long lasting effects

Precautionary statements:

P210	Keep away from heat/sparks/open flames/hot surfaces – No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Pressurised container – do not pierce or burn, even after use
P261	Avoid breathing vapour/spray.

P271 Use only outdoors or in well-ventilated area.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C

2.3 Other hazards

The mixture does not contain any vPvB or PBT substances.
Danger of bursting (explosion) when heated over 50°C.

SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS

3.2 Mixture:

HAZARDOUS INGREDIENTS	%W/W	CAS No EC No	REACH REG NO	HAZARD PICT/STATEMENTS
Hydrocarbon aerosol propellant (<0.1 butadiene)	25-50	68476-85-7 270-704-2	N/A	Flam gas1, H220
Hydrocarbons C7 n-alkanes, isoalkanes, cyclics	10-25	64742-49-0 927-510-4	01-2119475515-33	Flam liq 2 H225 Skin irritant 2 H315 Asp tox 1 H304 STOT SE3 H336 Aquat chronic 2 H411

3.3 Additional information

See sect 16 for full text of H phrases.

SECTION 4. FIRST AID MEASURES

4.1 Description of first aid measures:

Eyes: Remove contact lenses. Rinse with water immediately for at least 10 minutes. Obtain medical attention if any discomfort continues.

Skin: Remove severely contaminated clothing. Wash with soap and water. Obtain medical attention if any discomfort occurs.

Inhalation: Move to fresh air. Provide rest and warmth. If effects occur, obtain medical attention.

Ingestion: If swallowed, drink plenty of water. Do not induce vomiting. Obtain immediate medical attention.

4.2 Most important symptoms and effects, both acute and delayed.

The following symptoms may be apparent depending upon the routes of absorption as detailed in 4.1 above; skin/eye irritation, headache, nausea, dizziness, respiratory tract irritation. Ingestion –vomiting, diarrhoea, chemical pneumonitis, CNS depressant. Acute /long-term effects are further detailed in sect 11

4.3 Indication of any immediate medical attention and special treatment needed.

Treat symptomatically.

SECTION 5. FIRE FIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media: Powder, alcohol resistant foam. CO2, dry chemicals.

Unsuitable extinguishing media: Water stream

5.2 Special hazards arising from the substance or mixture

May produce oxides of carbon and other combustion products. Danger of explosion when heated. Contents will add to fuelling of fire. Solvent vapours may form explosive mixtures with air.

5.3 Advice for firefighters

Wear SCBA. Keep containers cool by spraying with water. Ventilate closed spaces before entering

SECTION 6. ACCIDENTAL RELEASE MEASURES:

6.1 Personal precautions, protective equipment and emergency procedures

Remove possible sources of ignition. Ensure sufficient ventilation. Wear suitable protective equipment as in Sect 8.

6.2 Environmental precautions.

Prevent from entering drainage systems or water courses.

6.3 Methods and material for containment and clearing

If spray or gas escapes, ensure plenty of fresh air / ventilation. Absorb spilled contents on inert material such as sand or earth - collect and dispose of as in Sect 13. Scrub area with detergent and water to prevent slippery residues.

6.4 Reference to other sections

For PPE and disposal see sections 8 and 13 respectively.

SECTION 7. HANDLING AND STORAGE:

7.1 Precautions for safe handling

Only use in areas with good ventilation. Keep away from any sources of ignition including live electrics. Do not use on hot surfaces. Wash hands after use and before eating. Remove contaminated clothing.

7.2 Conditions for safe storage, including any incompatibilities

Store in a cool, dry, ventilated area. Keep protected from direct sunlight and temperatures above 50°C.

7.3 Specific end use (s)

For anti seize / lubrication applications wherein aluminium complex grease is appropriate.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Workplace exposure limits

Ingredients	LTEL 8 Hr	STEL 15 min	Note
Hydrocarbon aerosol propellant (<0.1 butadiene)	1000 ppm	1250 ppm	EH40
Hydrocarbons C7 n-alkanes	500ppm	-	WEL

Biological limit value - Not established

PNECs, DNELs - Not established

8.2 Exposure controls

8.2.1 Appropriate engineering controls - Ensure good ventilation /local exhaust ventilation to keep airborne contaminants below exposure limits.

8.2.2 Personal protective equipment:

Eye / face protection - Safety goggles/glasses if there is a risk of eye contact.

Skin protection – Nitrile gloves (EN 374). See glove manufacturer data for glove selection and breakthrough time for use conditions.

Respiratory protection – Required if exceeding airborne conc limits. Type RPE (Organic vapour)

Thermal hazards – Not applicable

8.2.3 Environmental exposure controls – See sects 6,12, 13.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance/physical state:	Aerosol
Colour:	Black grease
Odour:	Mild, characteristic solvent
Odour threshold:	Not established
pH:	Not applicable
Melting /freezing point:	< 0 ⁰ C
IBP /boiling range:	< 0 ⁰ C
Flash Point	<0 ⁰ C
Evaporation rate:	Not established
Flammability (gas):	Extremely flammable
Upper /lower explosive limits:	1.8 – 9.4% by volume
Vapour pressure:	Approx 3 bar at 20 ⁰ C
Vapour density:	Not established
Relative density:	Not applicable
Solubility:	Negligible water miscibility
Partition coefficient (n-octanol/water):	Not established
Auto-ignition temperature:	Not established
Decomposition temperature:	Not established
Viscosity:	Not applicable
Explosive properties:	Not established
Oxidising properties:	None

SECTION 10 STABILITY AND REACTIVITY

10.1 Reactivity

No dangerous reactions known under normal conditions of use.

10.2 Chemical Stability

Stable under proper storage and handling conditions.

10.3 Possibility of chemical reactions

No dangerous reactions known.

10.4 Conditions to avoid

Heat, flame and other ignition sources .Pressurised container: Protect from sunlight and do not Expose to temperatures exceeding 50⁰C. Do not pierce or burn even after use.

10.5 Incompatible materials

Avoid contact with strong oxidising agents

10.6 Hazardous decomposition products

None when used as directed.

SECTION 11 TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

11.1.2. Mixtures

Acute toxicity	}	No data available
Irritation		
Corrosivity		
Sensitisation		
Repeated dose toxicity		
Carcinogenicity		
Mutagenicity		
Toxicity for reproduction		

Other information

May cause irritation and discomfort to eyes. Prolonged or repeated contact may cause skin irritation and dermatitis. High concentrations of vapours may cause drowsiness and dizziness. Ingestion may cause irritation to mouth and cause damage to respiratory system.

Hydrocarbons C7 n-alkanes

Toxicity / Effect	Endpoint	Value	Organism	Method	Notes
Acute Tox -Oral	LD50	>5000 mg/kg	Rat	OECD 401	Potential lung damage
Acute tox-Inhal	LC50	>23.3 mg/l	Rat -4hours	OECD 403	Throat irritation. CNS effect
Acute Tox- Derm	LD50	>2900 mg/kg	Rat	OECD 402	
Skin corrosion / Irritation					Irritant to skin & mucous membranes
Serious eye damage / Irritation					May cause serious eye damage
Sensitisation – Respiratory or Skin					No known sensitiser effect.
CMR effects					Not classified

Hydrocarbon aerosol propellant (<0.1% Butadiene)

General

In low concentrations may cause narcotic effects. Symptoms include dizziness, headache, nausea and loss of co-ordination.

SECTION 12 ECOLOGICAL INFORMATION:

Mixture

12.1 Toxicity

Harmful to aquatic life with long lasting effects

12.2 Persistence and degradability

12.3 Bioaccumulative potential

12.4 Mobility in soil

12.4 results of PBT and vPvB assessment

12.6 Other adverse effects.

No data available

Hydrocarbons C7 n-alkanes

12.1 Toxicity – Toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

Test	Duration	Organism	Method	Result	Notes
Aquatic -acute	48 hrs	Daphnia magna	EC50	3 mg/l	
Aquatic -chronic	21 days	Daphnia magna	NOEC	0.097 mg/l	

12.2 Persistence and degradability – Expected to be biodegradable.

12.3 Bioaccumulative potential – No data available.

12.4 Mobility in soil – Not soluble in water – will spread on water surface. Adsorbs on soil, low mobility

12.5 Results of PBT and vPvB assessment – Contains no PBT or vPvB components

12.6 Other adverse effects – None determined.

Hydrocarbon aerosol propellant (<0.1% Butadiene)

General

No known ecological damage.

SECTION 13 DISPOSAL CONSIDERATIONS:

13.1 Waste Treatment Methods

Empty containers must not be burnt or incinerated because of explosion hazard. Dispose of in accordance with local authority guidelines. Empty aerosol products may be recyclable via local authority.

SECTION 14. TRANSPORT INFORMATION:

14.1 UN number	1950
14.2 UN proper shipping name	Aerosols
14.3 Transport hazard class	2 (UN / IMDG)
ADR Classification code	5F
14.4 Packing group	None
14.5 Environmental hazards	Not applicable

SECTION 15. REGULATORY INFORMATION:

15.1 Safety, health and environmental regulations/legislation specific for the mixture

REACH - 1907/2006
CLP - 1272/2008
DPD - 199/45/EC
COSHH - 2002 (as amended)

15.2 Chemical safety assessment

A CSA has not been carried out for this mixture.

SECTION 16. OTHER INFORMATION:

Legend

LTEL	Long term exposure limit
STEL (SE)	Short term exposure limit (Single exposure)
STOT	Specific target organ toxicity
PNEC	Predicted no effect concentration
DNEL	Derived no effect level

Hazard statements –referred to in sect 3

H220	Extremely flammable gas
H225	Highly flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H411	Toxic to aquatic life with long-lasting effects

Classification methods used to derive classification of mixture

Classification according to calculation procedure detailed in EC1272/2008

Additional information

This safety data sheet has been produced based on information supplied by the manufacturers of the materials therein and is believed to be accurate. No warranty is expressed or implied by this information. It is for the user to satisfy themselves of the suitability of the product for their own purposes.