



## **FAST ACTING RELEASE SPRAY PENETRATING FLUID**

### *Product Overview*

*Fast acting penetrating and de-watering lubricant for the effective release of all corroded components. Its modern formulation enables the cleaning and lubrication of all metal parts in seconds and provides long-term protection against further contamination and corrosion.*

*The inclusion of fully dispersed, fine particle size PTFE also gives Pen Tech excellent lubrication qualities, even after the fluid film has disappeared.*

### *Typical Applications*

- **Recommended for the release of all threaded fasteners, joints and pipe couplings.**
- **Excellent lubrication of all mechanisms where penetration is required. After evaporation of the fluid film, a dry PTFE coating remains behind to give long life protection.**

### *Features and Benefits*

- Fast Acting
- PTFE for added lubricity
- De watering ability
- Effective in small quantities
- Protects and lubricates to prevent further problems.
- Non-Staining
- Effective on all metals
- Large 500ml can

### *Directions for Storage and Use*

*Product is to be stored in a clean, dry, storage area in its original sealed packaging. Container not to exceed 50°C*

*Shelf Life (unopened) – 3 years approx \**

*Spray onto seized parts allow a few seconds to penetrate and release*

*Caution: Pressurised container; protect from sunlight and do not expose to temperatures exceeding 50°C. Do not puncture or incinerate even when empty. Do not spray on any naked flame or any incandescent material*

#### **Disclaimer**

The data sheet is based on personal knowledge and experience and is given as a guideline to its possible uses. It does not take into account variables or conditions out of our control that can affect our product in any way. It is the users' sole responsibility to ensure that the product is suitable for the purpose for which it is being used and this data does not in any way form a warranty. If you are unsure of its suitability please contact us and we will be happy to discuss your needs and supply a sample for testing if required. New Tech Lubes Ltd is committed to supplying the best products and may therefore change the information in this specification at any time.

Available Sizes
500ml Aerosol
Available in bulk as Pen Tech Fluid

Available Grades

Physical Characteristics	
Density	0.92
Appearance	Clear Liquid
Container	Aerosol Spray
Propellant	Butane
Flashpoint	-400C

### *Safety Data Sheets*

*Safety data sheets are available for download from our website, scan the QR code to take you to our website*



[www.newtechlubes.com](http://www.newtechlubes.com)