




GDPRESS fittings offer reliable and consistent performance, combined with an easy installation process using common M-contour design and tooling compatability.

Each end has a toroidal seat, holding a rubber LBP (Leak before press) O-ring gasket. The fittings are installed with blue sleeves, which easily peel off after the pressing process.

All fittings are made from 316L (1.4404)
WRAS approved

Optional Fluoropolymer (FPM) O-rings are also available which offer higher heat and chemical resistance



**** DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL ****

Application	Operating temperature	Maximum operating pressure	Seal
Hot and cold potable water	0 to 100°C	16 BAR	EPDM
Heating water	0 to 100°C	16 BAR	EPDM
Cooling water without antifreeze agent	0 to 100°C	16 BAR	EPDM
Cooling water with antifreeze agent	-30 to +120°C	16 BAR	EPDM
Service/Treated water	0 to 100°C	16 BAR	EPDM
Rainwater/Grey and black water with a pH value of >6.0	0 to 100°C	16 BAR	EPDM
Extinguishing water	0 to 70°C	16 BAR	EPDM
Extinguishing water (wet/dry, dry)	0 to 70°C	16 BAR	FPM
Sprinklers	0 to 70°C	16 BAR	EPDM
Oils, Fuels and Chemicals	Please contact	Please contact	FPM