

Description

Superior Water Displacement Spray that lubricates and protects. A high performance water displacement spray which actively drives out moisture, even from hard-to-reach areas, leaving a fine lubricating film which protects against corrosion. This film enables future dismantling of equipment. Also an effective cleaner and degreaser. Does not contain silicone.

Benefits & Features

- Silicone free
- Powerful water displacement properties
- Leaves a shield against further moisture ingress
- Leaves a protective film, guarding against corrosion
- Good general lubrication for most components
- A rapid penetrant for seized fixings

Directions for Use

Shake can well before use. Spray onto area from 15-30cm. When used as a penetrant or for de-watering leave for a few minutes before continuing work. When applying as a protective coating allow to dry to form a film.

Technical Data

Appearance:	Off white low viscosity spray
Odour:	Slightly sweet solvent
Contents:	Blend of naphtha, waxes, solvents and oils with a hydrocarbon propellant
Flash Point:	<0°C
Solubility:	Insoluble in water
Temperature Range:	For use at ambient temperatures
Dielectric properties:	21.3 kV/mm
Flammability: Health & Safety:	Extremely Flammable Consult Safety Data Sheet (available at tygrisindustrial.com)
Storage:	Below 50°C
Pack Size:	12 x 400ml aerosols



Note

This technical data sheet is for general guidance purposes only and may contain information that is inappropriate for certain conditions of use. Accordingly, all recommendations and suggestions are made without guarantee. Further information is available from our Technical Department.