

Description

Specialist agent for highly effective silicone free release. An excellent alternative to silicone spray for the Plastic Moulding industry. It is a quick drying solvent and oil blend with a vegetable oil base, stable to 220°C. It is non-chlorinated and is easily removed by ordinary washing, facilitating further product finishing and making it as versatile as it is effective.

Benefits & Features

- Non-silicone content to allow for overpainting, lacquering, overprinting, gluing or welding
- No solvents for use with sensitive plastics
- Excellent surface slip
- Virtually odourless mild solvent which “flashes off”
- Effective where a high gloss finish is desirable
- Easily removed by conventional detergents
- Quick drying

Directions for Use

Ensure surface to be coated is clean and dry. Shake can well before use and spray a light even coat over the surface from a distance of 20-30cm. Allow to dry before placing components into use.

Technical Data

Appearance:	Colourless to pale yellow oily liquid
Odour:	Virtually odourless
Contents:	Blend of vegetable oil release agent and hydrocarbon propellants
Flash Point:	<0°C
Solubility:	Insoluble in water
Temperature Range:	0-180°C continuous, 200°C intermittent
Relative Density:	0.925
Flammability:	Extremely Flammable
Health & Safety:	Consult Safety Data Sheet (available at tygrisindustrial.com)
Storage:	Below 50°C
Pack Size:	12 x 400ml aerosols

Note

This technical data sheet is for general guidance purposes only and may contain information that is inappropriate for certain conditions of use. Accordingly, all recommendations and suggestions are made without guarantee. Further information is available from our Technical Department.

