

#### Description

A high temperature lubricant providing outstanding overall metal protection against heat, rust, seizure and corrosion. Resistance to water and acids is high and it will not burn off under extreme stress. For use on threaded components, pins, valve stems in a range of materials including austenitic stainless steel. Used on brake callipers and the back of brake pads it will help eliminate brake squeal.

#### Benefits & Features

- Effective up to 1100°C
- Water and acid resistant
- Use on a wide range of metals
- Prevents seizure of threaded parts
- Will not burn or wash off
- Eliminates brake squeal
- Assists in assembly and disassembly of components

#### Directions for Use

Shake can well before use. Spray component from a distance of 15 to 30cm. Wipe off excess. **Do not apply to friction materials and pads.**

#### Technical Data

Appearance:	Soft copper (orange-red) coloured grease
Odour:	Oily solvent
Contents:	Blend of copper paste, calcium grease, mineral oils, and hydrocarbon propellants. No lead, silicone or chlorinated solvents
Flash Point:	-60°C
Solubility:	Insoluble in water
Temperature Range:	150°C to 1100°C
Relative Density:	
Flammability:	Extremely Flammable
Health & Safety:	Consult Safety Data Sheet (available at <a href="http://tygrisindustrial.com">tygrisindustrial.com</a> )
Storage:	Below 50°C
Pack Size:	12 x 400ml aerosols



#### Note

This technical data sheet is for general guidance purposes only and may contain information that is inappropriate for certain conditions of use. Accordingly, all recommendations and suggestions are made without guarantee. Further information is available from our Technical Department.