TECHNICAL DATA SHEET



GRAFFITI REMOVER

Description

Targeted action for quick and easy renovation. A powerful solvent and wetting agent based formulation making the removal of unwanted markings quick and effective, with minimal effect on the substrate. Will remove graffiti from plastics, wood, metal, glass, and most painted surfaces.

Benefits & Features

- · Use on a wide range of surfaces including many plastics
- Wetting agents make for effective penetration
- Methylene Chloride free
- Easy to apply
- Rapid penetration
- Fast drying

Directions for Use

Shake can well before use and spray onto surface from a distance of 20 to 25cm. Allow a few minutes to wet and penetrate the graffiti and wipe off. Can also be rinsed off with water. **Check compatibility on plastics. Do not use on hot surfaces where evaporation may occur before penetration.**

Technical Data

Appearance: Clear liquid
Odour: Solvent

Contents: Blend of 2-methoxy-1-methyl ethyl

acetate, acetone, n-butyl acetate, methylal, 1,3 dioxolane and fatty alcohol ethoxylate with butane/propane propellant

Flash Point: <0°C

Solubility:

Temperature Range: Designed for use at ambient temperatures

Relative Density: 0.87

Flammability: Extremely Flammable

Health & Safety: Consult Safety Data Sheet (available at

tygrisindustrial.com)

Storage: Below 50°C

Pack Size: 12 x 400ml aerosols

GRAFFITI REMOVER Penetration ist Removal Graffiti

Note

This technical data sheet is for general guidance purposes only and may contain information that is inappropriate for certain conditions of use. Accordingly, all recommendations and suggestions are made without guarantee. Further information is available from our Technical Department.

