TECHNICAL DATA SHEET



GRAFFITI REMOVER - VISCOUS

Description

Remove graffiti fast with this thickened formula for use on vertical surfaces. This thickened powerful graffiti remover is effective in the removal of paint graffiti, ink and felt tip, particularly on vertical surfaces or areas where the slow evaporation aids in penetration for capable erasure of unwanted marks.

Benefits & Features

- Thixotropic to aid in clinging to vertical surfaces Water washable
- Slow drying for better penetration
- · Removes paint, biro, felt tip pin
- Easily applied
- Non-chlorinated
- · Also effective in the removal of old gaskets

Directions for Use

Spray directly onto affected area from 20-25cm, allow a short time for product to penetrate, and wipe away to remove graffiti. Rinse as necessary. **Test a small unobtrusive area on coated or painted surfaces first to ensure compatibility. Not suitable for use on uPVC or polycarbonate.**

Technical Data

Appearance: Clear foaming spray

Odour: Solvent

Contents: Blend of acetone, hydrocarbon wax,

thickeners and odourless kerosene in a

dimethyl ether propellant

Flash Point: <0°C

Solubility: Insoluble in water

Temperature Range: Designed for use at ambient temperatures

Relative Density: 0.95

Flammability: Extremely Flammable

Health & Safety: Consult Safety Data Sheet (available at

tygrisindustrial.com)

Storage: Below 50°C

Pack Size: 12 x 400ml aerosols



Note

This technical data sheet is for general guidance purposes only and may contain information that is inappropriate for certain conditions of use. Accordingly, all recommendations and suggestions are made without guarantee. Further information is available from our Technical Department.

