



SIZE BSPP (D)	SIZE BSPP (C)	PRODUCT CODE	PRESSURE (BAR)	A	B	F A/F	KG EACH
1/4	1/8	RAFM0402P	350	25.6	8.1	19.1	0.045
3/8	1/4	RAFM0604P	350	31.3	11.1	22.2	0.059
1/2	1/4	RAFM0804P	315	35.1	11.1	28.6	0.11
1/2	3/8	RAFM0806P	315	36.1	12.1	28.6	0.14
3/4	1/2	RAFM1208P	250	44.1	14.1	31.7	0.19

**\*\* DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL \*\***

NERO's range of Reducing Adaptors are available in BSPP thread form with a 60° internal cone on the male end recessed to accept a Bonded Washer

Made from hexagon bar with a flat sealing face on the female end

Pressure rating up to 350 BAR (size dependant)

Can be supplied with 2.2 Certificate of Conformity - upon request

BSPP Male & Female threads are to ISO 228/1  
60° internal cone to BS 5200

At sizes 1/8" to 1/2" the fitting is a Gauge Adaptor

**We stock a wide range of Hydraulic Fittings to suit your requirements**



**We also keep Equal Adaptor versions of this fitting + Bonded Washers in our Hydraulic range**

