

RENOLIT MP PLUS

Adhesive Multipurpose Grease

Description

RENOLIT MP PLUS is a heavy-duty, adhesive, aging and water resistant, lithium soap based multipurpose grease.

RENOLIT MP PLUS offers outstanding corrosion protection and excellent low temperature characteristics. It is smooth and work-stable.

Application

RENOLIT MP PLUS is the perfect universal lubricating grease for all applications in cars, trucks and machinery. RENOLIT MP PLUS can also be used as battery terminal grease.

Advantages

- Extremely adhesive
- Aging resistant
- Water resistant
- Extraordinary corrosion protection
- Mechanically loadable

Shelf Life

The minimum shelf life is 36 months if the product is properly stored between 0°C and 40°C in its unopened original container in a dry place. The indication of a minimum shelf life does not include any guarantee of durability.

RENOLIT MP PLUS

Adhesive Multipurpose Grease

Characteristics

Properties	Unit	Data	Test method
Classification	-	KP 2 K-30 ISO-L-X-CCEB 2	DIN 51 502 ISO 6743-9
Colour	-	Light brown	-
Thickener	-	Lithium-soap	-
Dropping point	°C	≥ 180	IP 396
Worked penetration (Pw 60)	0.1 mm	265 - 295	DIN ISO 2137
NLGI grade	-	2	DIN 51 818
Corrosion protection properties (Emcor-method)	degree of corr.	0 - 0	DIN 51 802
Water resistance	eval.-stage	1 - 90	DIN 51 807
Four ball method, welding load	N	2600	DIN 51 350-4
Flow pressure at +20°C at -20°C at -35°C	hPa	≤ 100 ≤ 400 ≤ 1600	DIN 51 805-2
Base oil viscosity at +40 °C	mm ² /s	100	DIN 51 562-1
Temperature range Short term	°C	-30 to +120 140	DIN 51 825

PI 5-4422e, Page 2/2, PM 5, 10/16UK