
View product details on medias

18.09.2026, 10:13:20 BST

SCHAEFFLER





RUS19069

Linear recirculating roller bearing unit

Linear roller bearings with spacer elements
RUS..

Technical information





Your current product variant

Size Code	19069

Main Dimensions & Performance Data


L_{tot}	74 mm	Total length
L	70.4 mm	
B	27 mm	Width
H	19 mm	Height
C	42,000 N	Basic dynamic load rating
C_0	66,000 N	Basic static load rating
≈m	0.208 kg	Weight

The data sheet only contains an overview of the technical data of the selected product. Please refer to the additional documentation for this product. For further information, please use the following link on our website: Contact form

View product details on medias

18.09.2026, 10:13:20 BST

SCHAEFFLER



Mounting dimensions

L_1	43.8 mm	Mounting dimension
J_B	20.6 mm	Mounting dimension
Tol J_B	± 0.1 mm	Tolerance
J_L	25.5 mm	
Tol J_L	± 0.1 mm	Tolerance
H_1	0.2 mm	
L_4	50 mm	Minimum support length
L_W	10 mm	
H_4	15.2 mm	
T_5	6.2 mm	
G_1	M4	Fixing screws top (DIN ISO 4762-12.9)
G1 M_A	5 Nm	Tightening torrque fixing screws
K_3	M3	Fixing screws below (DIN ISO 4762-12.9)
K3 M_A max	1.8 Nm	Tightening torque fixing screws
D_2	3.5 mm	
	6 mm	

Related products

	VUS19069-A	Adjustment gib
	UG6628, UGN6628, UZ6628, UZN6628, UFK3210, UFB4710	Suitable Guide rail

The data sheet only contains an overview of the technical data of the selected product. Please refer to the additional documentation for this product. For further information, please use the following link on our website: Contact form