



RUS19105

Linear recirculating roller bearing unit

Linear roller bearings with spacer elements
RUS..

Technical information




Your current product variant

Size Code	19105
-----------	-------

Main Dimensions & Performance Data

L _{tot}	109 mm	Total length
L	105.5 mm	
B	27 mm	Width
H	19 mm	Height
C	68,000 N	Basic dynamic load rating
C ₀	123,000 N	Basic static load rating
≈m	0.29 kg	Weight



Mounting dimensions

L 1	79 mm	Mounting dimension
J B	20.6 mm	Mounting dimension
Tol J B	± 0.1 mm	Tolerance
J L	50 mm	
Tol J L	± 0.1 mm	Tolerance
H 1	0.2 mm	
L 4	85 mm	Minimum support length
L W	10 mm	
H 4	15.2 mm	
T 5	6.2 mm	
G 1	M4	Fixing screws top (DIN ISO 4762-12.9)
G1 M A	5 Nm	Tightening torque fixing screws
K 3	M3	Fixing screws below (DIN ISO 4762-12.9)
K3 M A max	1.8 Nm	Tightening torque fixing screws
D 2	3.5 mm	
	6 mm	

Related products

VUS19105-A	Adjustment gib
UG6628, UGN6628, UZ6628, UZN6628, U FK3210, UFB4710	Suitable Guide rail