
View product details on medias

18.09.2026, 10:10:53 BST

SCHAEFFLER





RUS26102

Linear recirculating roller bearing unit

Linear roller bearings with spacer elements
RUS..

Technical information






Your current product variant

Size Code	26102

Main Dimensions & Performance Data

L_{tot}	106 mm	Total length
L	102.4 mm	
B	40 mm	Width
H	26 mm	Height
C	95,000 N	Basic dynamic load rating
C_0	151,000 N	Basic static load rating
≈m	0.6 kg	Weight

The data sheet only contains an overview of the technical data of the selected product. Please refer to the additional documentation for this product. For further information, please use the following link on our website: Contact form



Mounting dimensions

L_1	68.9 mm	Mounting dimension
J_B	30 mm	Mounting dimension
Tol J_B	± 0.1 mm	Tolerance
J_L	44 mm	
Tol J_L	± 0.1 mm	Tolerance
H_1	0.2 mm	
L_4	79 mm	Minimum support length
L_W	14 mm	
H_4	21 mm	
T_5	10.2 mm	
G_1	M6	Fixing screws top (DIN ISO 4762-12.9)
G1 M_A	17 Nm	Tightening torrque fixing screws
K_3	M4	Fixing screws below (DIN ISO 4762-12.9)
K3 M_A max	5 Nm	Tightening torque fixing screws
D_2	4.9 mm	
	6 mm	

Related products

	VUS26102-A	Adjustment gib
	UG9741, UGN9741-A, UZ9741, UZN9741-A, UFK4710, UFB6412	Suitable Guide rail

The data sheet only contains an overview of the technical data of the selected product. Please refer to the additional documentation for this product. For further information, please use the following link on our website: Contact form