



WIRE ROPE DRESSING & LUBRICANT ROPE TECH

Product Overview

Rope Tech is a wire rope lubricant that has been constructed to meet the lubrication, corrosion protection, and high load requirements of wire ropes operating in the most adverse conditions. Rope Tech will penetrate between rope strands and its thin surface coating will provide excellent adhesion and a marked reduction in abrasive pick up.

Typical Applications

- **Mobile Cranes**
- **Drag Lines**
- **Hoists**
- **Dockside & Ships Cranes**

Features and Benefits

- Provides Internal & External protection
- Solid lubricants reduce wear between strands
- Can be applied thinly to reduce fling off
- Water repellent to prevent corrosion
- Does not contain solvents

Directions for Storage and Use

Product is to be stored in a clean, dry, storage area in its original sealed packaging.

Shelf Life (unopened) – 3 years approx *

*Some bleeding may occur, thorough mixing will homogenise the mixture to its original state.

Product can be applied by brush, applicator or automatic lubrication system. Do not over lubricate.

Do not mix with other lubricants if compatibility is not known, for best results purge system of other lubricants. Apply to clean, dry parts only.

Disclaimer

The data sheet is based on personal knowledge and experience and is given as a guideline to its possible uses. It does not take into account variables or conditions out of our control that can affect our product in any way. It is the users' sole responsibility to ensure that the product is suitable for the purpose for which it is being used and this data does not in any way form a warranty. If you are unsure of its suitability please contact us and we will be happy to discuss your needs and supply a sample for testing if required. New Tech Lubes Ltd is committed to supplying the best products and may therefore change the information in this specification at any time.

Available Sizes
12.5kg Pail
25kg Pail
50kg Keg
180kg Barrel

Physical Characteristics	
Appearance	Smooth Grease Grey / black fluid grease
NLGI	00
Timken OK load (IP 326)	20kgs (44lbs)
Dynamic corrosion resistance	0:0 (EMCOR) (IP220)
Operating temperature range	-40°C to +120°C

Available Grades
NLGI 00

Safety Data Sheets

Safety data sheets are available for download from our website, scan the QR code to take you to our website



www.newtechlubes.com