SAFESTOCK945



Sales - North
Sandy Purnell
sandy.purnell@safe-stock.co.uk
07867 143697

Sales - South

Tony Goodridge

tony.goodridge@safe-stock.co.uk

07974 201565





Innovative Multifunctional Vending Machine, adapted to the management of a large number of commodity indexes.



ADVANTAGES

- 24/7 access.
- Drop in the consumption of products by up to 50%.
- Large capacity, up to 945 compartments in the machine.
- 4 options for loading products into the machine.
- 21" touch screen with modern and intuitive interface.
- 9 configurations for height and width of compartments.
- Built-in RFID reader, barcode and QR code scanner.
- Monitoring of current status via the IRSystem web application.
- Modularity allows to combine devices into sets.

IR SYSTEM APPLICATION


We offer proprietary IRSystem software tailored to the individual needs of the customer for each vending machine, which opens up unlimited possibilities for remote process management. IRSystem enables data migration and fast communication between the server and machine.

- possibility of integration with systems such as ERP, GERP, SAP, etc.
- generating of automatic reports and orders
- actual preview of the inventories available in the machine
- management of authorisation of employee access to the vending machine



IRstock 945 is a modern and self-service vending machine used for product distribution. The rotating, sturdy drum gives you the ability to storage up to 945 unique items. Ease of operation is provided by 21" touch screen with modern and intuitive interface. Four product loading options enable even faster and simpler filling the machine. The IRstock 945 has a built-in RFID reader, barcode and QR code scanner.

TECHNICAL SPECIFICATIONS				
Height [mm]	2 000			
Width [mm]	1 100			
Depth [mm]	840			
Voltage [V]	230 VAC - 50 Hz			
Power usage [W]	5/80			
Max. drum load [kg]	350			
Weight [kg]	530			
Temp. [°C]	from 5 to 70			
DRUM CONFIGURATIONS				



COMPARTMENS CONFIGURATIONS AND DIMENSIONS				
NUMBER OF COMPARTMENTS	A HEIGHT [MM]	B WIDTH [MM]	C DEPTH [MM]	D WIDTH [MM]
945	80	50	295	12
630	80	80	295	18
315	80	160	295	35
495	160	50	295	12
330	160	80	295	18
165	160	160	295	35
315	245	50	295	12
210	245	80	295	18
105	245	160	295	35