



CALCIUM COMPLEX GREASE SOLO EP



Product Overview

Solo EP is a premium quality lubricating grease for use in severe conditions; the product is highly water repellent and has good chemical resistance. Solo EP is based on mineral oil thickened with a complex calcium sulphonate that endows the grease with a very high melting point, this makes the product very thermally stable and it may be recommended for many high temperature applications

Typical Applications

- **Anti-friction and plain bearings for use in industrial and automotive applications**
- **Applications around fresh or salt water**
- **Applications subjected to chemical attack**

Features and Benefits

- *Very good thermal stability.*
- *Exceptionally water repellent*
- *Chemical resistance*
- *Good performance under high loads*
- *Excellent rust and corrosion prevention*

Directions for Storage and Use

Product is to be stored in a clean, dry, storage area in its original sealed packaging.

*Shelf Life (unopened) – 3 years approx **

**Some bleeding may occur, thorough mixing will homogenise the mixture to its original state.*

Product can be applied by brush, applicator or automatic lubrication system.

Do not mix with other lubricants if compatibility is not known, for best results purge system of other lubricants. Apply to clean, dry parts only.

Disclaimer

The data sheet is based on personal knowledge and experience and is given as a guideline to its possible uses. It does not take into account variables or conditions out of our control that can affect our product in any way. It is the users' sole responsibility to ensure that the product is suitable for the purpose for which it is being used and this data does not in any way form a warranty. If you are unsure of its suitability please contact us and we will be happy to discuss your needs and supply a sample for testing if required. New Tech Lubes Ltd is committed to supplying the best products and may therefore change the information in this specification at any time.

Available Sizes
400ml Cartridge
5kg Pail
12.5kg Pail
25kg Pail
50kg Keg
180kg

Available Grades
NGL12

Physical Characteristics	
Colour	Dark Brown
Drop Point	>300°C
Weld Load	500Kg
Density	0.94
Water Washout	<2% - 30hrs @ 60°C
Salt Water Washout	<2% - 30hrs @ 60°C
Base Oil Viscosity 40°C	440-460cst
Temp Range	-30°C to +180°C

Safety Data Sheets

Safety data sheets are available for download from our website, scan the QR code to take you to our website



www.newtechlubes.com