

Description

Powerful penetrant for releasing seized components. A kerosene based penetrating fluid for the fast release of components and fasteners which have seized as a result of corrosion. Highly effective wetting agents cause the solution to rapidly spread and penetrate, even on vertical surfaces.

Benefits & Features

- Quickly releases corrosion from rusted fasteners
- Rapid penetration
- Effective on vertical surfaces
- Leaves a residue of lubricant for future dismantling
- Extreme pressure and anti wear properties
- For use on fastenings, hinges and locks etc

Directions for Use

Brush a quantity of penetrating oil onto the surface to be treated, leave for a few minutes and release with normal tools.

Technical Data

Appearance:	Green tinted liquid
Odour:	Typical kerosene odour
Contents:	Blend of kerosene, solvent and low viscosity lubricating oil
Flash Point:	56°C
Solubility:	Insoluble in water, soluble in most organic solvents
Relative Density:	0.86
Viscosity:	4.0cSt @ 40°C
Flammability:	Flammable
Health & Safety:	Consult Safety Data Sheet (available at tygrisindustrial.com)
Storage:	Store in a cool, ventilated location
Pack Size:	4 x 5ltr



Note

This technical data sheet is for general guidance purposes only and may contain information that is inappropriate for certain conditions of use. Accordingly, all recommendations and suggestions are made without guarantee. Further information is available from our Technical Department.