T GRIS

L2 GP LITHIUM GREASE **TG7550**

Description

A premium quality multi-purpose grease for use in all anti-friction and plain bearings. The incorporation of oxidation and rust inhibitors provides good corrosion protection and long life. Used extensively for applications throughout industry and the automotive sector.

Benefits & Features

- High degree of corrosion protection
- Highly versatile multi purpose grease

Directions for Use

Apply manually or by filled grease gun.

Technical Data

Appearance:	Smooth pale brown grease
NLGI Classification:	2
Base Oil:	Blend of solvent refined mineral oil
Base Oil Viscosity:	110cSt @ 40°C, 9cSt @ 100°C
Thickener: Worked	Lithium soap
Penetration:	265 to 295
Resistance to Corrosion:	0:0
Water Washout:	<5% at 39°C
Relative Density:	0.91
Solubility:	Insoluble in water
Temperature Range:	-20° to 120°C. Melts above 200°C
Oil Separation:	5% max

Note

This technical data sheet is for general guidance purposes only and may contain information that is inappropriate for certain conditions of use. Accordingly, all recommendations and suggestions are made without guarantee. Further information is available from our Technical Department.



31 Kyle Road, Irvine KA12 8LE Tel: +44 (0) 1294 311 066 technical@tygrisindustrial.com