

Description

Synthetic grease for high temperature applications. A premium quality lithium complex thickened grease for use in plain and anti friction bearing surfaces in high temperature applications over long periods of time without leaving a dry residue. Providing excellent lubrication also at sub-zero and ambient temperatures, this is an extremely versatile grease.

Benefits & Features

- High temperature resistance with extended lubrication intervals
- Reduces carbon deposits at high temperatures
- Extreme pressure additives and PTFE for long component life
- Excellent corrosion and humidity resistance

Directions for Use

Apply by grease gun.

Technical Data

Appearance:	Smooth brown grease
NLGI Classification:	2
Base Oil:	Synthetic hydrocarbon
Thickener:	Lithium complex
Four Ball Weld Load:	355kg
Solid Lubricant:	PTFE
Corrosion (ASTM D130):	1b
Drop Point (ASTM D2265):	>250°C
Load Wear Index:	68kg
dN Factor:	750,000
Storage:	1° to 40°C
Relative Density:	0.96
Solubility:	Insoluble in water
Temperature Range:	-50° to 220°C
Pack Sizes:	12 x 400g

Note

This technical data sheet is for general guidance purposes only and may contain information that is inappropriate for certain conditions of use. Accordingly, all recommendations and suggestions are made without guarantee. Further information is available from our Technical Department.