

TITAN SUPERSYN F Eco-DT SAE 5W-30

Ultra High Performance, extreme fuel-economy engine oil especially suitable for Ford DuraTorq-Diesel engines. Optimum cold starting and lower oil consumption.

Description

TITAN SUPERSYN F Eco-DT SAE 5W-30 is a highly energy conserving multigrade passenger car engine oil suitable for Ford diesel and gasoline engines. The most up to date technology of TITAN SUPERSYN F Eco-DT SAE 5W-30 is absolutely beneficial for current engine technology. TITAN SUPERSYN F Eco-DT SAE 5W-30 provides advantages in economy, durability and exhaust gas emissions. TITAN SUPERSYN F Eco-DT SAE 5W-30 afford excellent durability for long life performance, wear protection and cold temperature performance.

Application

TITAN SUPERSYN F Eco-DT SAE 5W-30 is developed for use in Ford diesel vehicles and recommended additionally for use in gasoline passenger cars. Further TITAN SUPERSYN F Eco-DT SAE 5W-30 can be used for other Manufacturers according ACEA specification and manufacturer recommendation.

TITAN SUPERSYN F Eco-DT SAE 5W-30 shall be used for gasoline engines with and without turbo charger as well as indirect and direct injection. It is miscible and compatible with conventional branded engine oils. However, mixing with other engine oils should be avoided in order to fully utilize the product's benefits. A complete oil change is recommended when converting to TITAN SUPERSYN F Eco-DT SAE 5W-30. For information on product safety and proper disposal please refer to the latest Material Safety Data Sheet.

Advantages/Benefits

- High thermal and oxidative stability
- Sludge protection
- Sustainable fuel economy
- Very good cold start behaviour
- Excellent wear protection
- Recommended for Ford diesel passenger cars
- Suitable for selected hybrid vehicles depending on OEM requirements

Specifications

- ACEA A5/B5
- API SL
- FORD WSS-M2C913-C
- FORD WSS-M2C913-D

Approvals

- JAGUAR LAND ROVER STJLR.03.5003

FUCHS Recommendations

- ACEA A1/B1
- API CF
- CHRYSLER MS 6395
- FORD WSS-M2C913-A
- FORD WSS-M2C913-B
- IVECO 18-1811 CLASSE S1/S2
- JAGUAR M2C913-B
- RENAULT RN0700

PI60535e, PMA, 28.06.2021, Page 1

TYPICAL CHARACTERISTICS

Density at 15 °C	DIN 51757	0.852 g/ml
SAE grade	SAE J300	5W-30
Kinematic Viscosity at 40°C	DIN 51562-1	49.5 mm ² /s
Kinematic Viscosity at 100°C	DIN 51562-1	9.5 mm ² /s
Viscosity index	DIN ISO 2909	179
HTHS	CEC L-036-90	3.0 mPa*s
Pour point	DIN ISO 3016	-36 °C
Sulphated ash	ASTM D874	≤ 1.6 % m/m
Product dyeing	DIN 10964	none

PI60535e, PMA, 28.06.2021, Page 2