



CVJ STRETCH BOOT INSTALLATION TOOL

MODEL NO: **VS701**

Thank you for purchasing a Sealey product. Manufactured to a high standard, this product will, if used according to these instructions, and properly maintained, give you years of trouble free performance.

IMPORTANT: PLEASE READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS & CAUTIONS. USE THE PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE AND/OR PERSONAL INJURY AND WILL INVALIDATE THE WARRANTY. KEEP THESE INSTRUCTIONS SAFE FOR FUTURE USE.



Refer to instructions



Wear eye protection



Wear protective gloves

1. SAFETY

1.1 GENERAL SAFETY

- ✓ Carefully read these operating and safety instructions before using the boot tool. Keep them for future reference.
- ✓ This tool should only be used by properly trained operators.
- ✓ Keep the work area clean, uncluttered and ensure there is adequate lighting.
- ✓ Maintain correct balance and footing. Ensure the floor is not slippery and wear non-slip shoes.
- ✓ Remove ill fitting clothing. Remove ties, watches, rings, and other loose jewellery, and contain and/ or tie back long hair.
- ✓ Keep children and unauthorised persons away from the working area.
- ✓ Keep the boot tool away from fire, heat and chemicals.
- * **DO NOT** use the boot tool for any purpose other than that for which it is designed.
- * **DO NOT** operate the boot tool when you are tired, under the influence of alcohol, drugs or intoxicating medication.
- ☐ **WARNING!** Ensure Health & Safety, local authority, and general workshop practice regulations are adhered to when using this equipment.

1.3 MECHANICAL SAFETY

- ✓ Maintain the boot tool in good condition (use an authorised service agent).
- ✓ If the tool falls or is knocked, stop operation and check for any damage.
- * **DO NOT** operate the boot tool if any parts are damaged as this may cause failure and/or personal injury.

1.4 OPERATIONAL SAFETY

- ✓ Working with the boot tool requires protective equipment including safety shoes, work gloves and safety goggles. **DO NOT** bring the tool close to the face while operating.
- ✓ When operating the boot tool, to open a CV rubber boot, turn the tool away from your face and body.

2. INTRODUCTION

Enables installation of CVJ boot in situ without splitting the drive train. Slim design ideal for fitting CVJ boots where access is limited. Suitable for use with all Sealey CVJ stretch boots. Length 442mm. Maximum CVJ diameter Ø122mm. Use in conjunction with Sealey VS705.

3. SPECIFICATION

Model No:..... VS701
Length: 442mm
Maximum Joint Diameter:..... Ø122mm

4. OPERATION

- ☐ **WARNING!** The boot tool is designed for the installation of a flexible Sealey universal rubber CV boots only and should be used with no other products and for no other purpose.
- 4.1. Use cleaner to clean out the C.V joint.
- 4.2. Fill with grease.
- 4.3. Put universal rubber boot on the Sealey VS701 see fig.1 and spray rubber protection fluid on it.
- 4.4. Spray rubber protection fluid on Sealey VS705 (not supplied) in order to make Sealey VS705 surface smooth (fig.2)
- 4.5. Use the Sealey VS701 to put boot to the bottom of Sealey VS705 slowly (fig.3). Press C.V boot over C.V joint (fig.4).
- 4.6. Once it has been pushed into place the VS705 can be removed easily (fig.5).
- 4.7. Remove the Sealey VS701 (fig.6).
- 4.8. Fix boot into a suitable location and secure with steel clips to secure the boot, in some cases you may have to trim the boot to fit. (fig.7).










fig.1



5. MAINTENANCE

- 5.1. Apart from keeping the boot tool clean there is no routine maintenance required.
- 5.2. Use genuine parts only. *Non-authorized parts may be dangerous and will invalidate the warranty.*



ENVIRONMENT PROTECTION

Recycle unwanted materials instead of disposing of them as waste. All tools, accessories and packaging should be sorted, taken to a recycling centre and disposed of in a manner which is compatible with the environment. When the product becomes completely unserviceable and requires disposal, drain any fluids (if applicable) into approved containers and dispose of the product and fluids according to local regulations.



REGISTER YOUR PURCHASE HERE

Note: It is our policy to continually improve products and as such we reserve the right to alter data, specifications and component parts without prior notice.

Important: No Liability is accepted for incorrect use of this product.

Warranty: Guarantee is 12 months from purchase date, proof of which is required for any claim.

Sealey Group, Kempson Way, Suffolk Business Park, Bury St Edmunds, Suffolk. IP32 7AR

 01284 757500

 sales@sealey.co.uk

 www.sealey.co.uk