



**SAFETY DATA SHEET**  
**According to EC Regulations 1907/2006 & 1272/2008**  
**NTL SDS 1011A-1.0**  
**August 2016**

Unit 3 & 4  
Harrison Drive Ind Est  
Worksop, Nottinghamshire  
UK, S81 9RL  
  
t. 01909 730900  
f. 01909 730909  
e. info@newtechlubes.com  
w. www.newtechlubes.com

🐦 @newtechlubes.com

## WHITE MAINTENANCE GREASE

### SECTION 1. IDENTIFICATION OF THE PREPARATION AND THE COMPANY / UNDERTAKING

- |  |   |
|--|---|
| <b>1.1 Product Name:</b>               | White Maintenance Grease Aerosol  |
| <b>1.2 Identified uses:</b>            | Lubricant   |
| <b>Use's advised against</b>           | None known.   |
| <b>1.3 Details of supplier of SDS:</b> | New Tech Lubes Ltd, Unit 3 Harrison Drive Ind Est, Worksop Notts, S81 9RL |
| <b>E Mail (competent person)</b>       | info@newtechlubes.com   |
| <b>1.4 Emergency Telephone:</b>        | +44 (0)1909 730900 (09.00 -17.00 GMT Monday to Friday)                    |

### SECTION 2. HAZARDS IDENTIFICATION

**2.1 Classification of the substance /mixture:**

**2.1.1 Regulation EC 1272/2008:**

Aerosol (cat 1)	H222
Skin irritant (cat 2)	H315.
Aquatic chronic (cat 3)	H412

**2.2 Label elements:**



**Signal word(s):** Danger

<b>Hazard statements:</b>	H222	Extremely flammable aerosol
	H229	Pressurised container: may burst if heated
	H315	Causes skin irritation.
	H412.	Harmful to aquatic life with long lasting effects

**Precautionary statements:**

P210	Keep away from heat/sparks/open flames/hot surfaces – No smoking.
P211	Do not spray on an open flame or other ignition source.
P243	Take precautionary measures against static discharge.
P251	Pressurised container – do not pierce or burn, even after use
P261	Avoid breathing vapour/spray.
P271	Use only outdoors or in well-ventilated area.
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C
EUH066	Repeated exposure may cause skin dryness or cracking

**2.3 Other hazards**

The mixture does not contain any vPvB or PBT substances.  
 Danger of bursting (explosion) when heated over 50°C.

**SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS****3.1 Mixture:**

HAZARDOUS INGREDIENTS	%W/W	CAS No EC No	REACH REG NO	HAZARD PICT/STATEMENTS
Hydrocarbon aerosol propellant (<0.1 butadiene)	25-50	68476-85-7 270-704-2	N/A	Flam gas1, H220
Hydrocarbons,C7-C9 Isoalkanes <2% aromatics	10-25	– . 921-728-3	01-2119471305-42	Flam liq 3, H226 Asp tox 1, H304 Skin irrit 2. H315 Aq chronic 2, H411 EUH066
Propan-2-ol	1-5	67-63-0 200-661-7	01-2119457558-25	Flam liq 2, H225 Eye irritant 2, H319 STOT SE3, H336

**3.2 Additional information**

See sect 16 for full text of H phrases.

**SECTION 4. FIRST AID MEASURES****4.1 Description of first aid measures:**

Eyes:	Remove contact lenses. Rinse with water immediately for at least 10 minutes. Obtain medical attention if any discomfort continues.
Skin:	Wash skin with soap and water. If grease has been injected under the skin, seek Medical advice immediately
Inhalation:	Move to fresh air. Provide rest and warmth. If effects occur, obtain medical attention.
Ingestion:	If swallowed, drink plenty of water. Do not induce vomiting. Obtain immediate medical attention.

**4.2 Most important symptoms and effects, both acute and delayed.**

The following symptoms may be apparent depending upon the routes of absorption as detailed in 4.1 above; skin/eye irritation, headache, nausea, dizziness, respiratory tract irritation.. Resultant acute /long-term effect to the CNS, dermatitis, vomiting, diarrhoea and are further detailed in sect 11

#### **4.3 Indication of any immediate medical attention and special treatment needed.**

Excessive exposure may aggravate pre-existing asthmatic and other respiratory disorders.

### **SECTION 5. FIRE FIGHTING MEASURES**

#### **5.1 Extinguishing media:**

Suitable extinguishing media: Powder, alcohol resistant foam. CO2, dry chemicals.

Unsuitable extinguishing media: Water stream

#### **5.2 Special hazards arising from the substance or mixture**

May produce oxides of carbon and other combustion products. Danger of explosion when heated.

Contents will add to fuelling of fire. Solvent vapours may form explosive mixtures with air.

#### **5.3 Advice for fire fighters**

Wear self-contained breathing apparatus. Keep containers cool by spraying with water. Ventilate closed spaces before entering

### **SECTION 6. ACCIDENTAL RELEASE MEASURES:**

#### **6.1 Personal precautions, protective equipment and emergency procedures**

Remove possible sources of ignition. Ensure sufficient ventilation. Wear suitable protective equipment as in Sect 8.

#### **6.2 Environmental precautions.**

Prevent from entering drainage systems or water courses.

#### **6.3 Methods and material for containment and clearing**

If spray or gas escapes, ensure plenty of fresh air / ventilation. Absorb spilled contents on inert material such as sand or earth - collect and dispose of as in Sect 13. Scrub area with detergent and water to prevent slippery residues.

#### **6.4 Reference to other sections**

For PPE and disposal see sections 8 and 13 respectively.

### **SECTION 7. HANDLING AND STORAGE:**

#### **7.1 Precautions for safe handling**

Only use in areas with good ventilation. Keep away from any sources of ignition including live electrics. Do not use on hot surfaces. Take precautions against static discharge. Wash hands after use and before eating. Remove contaminated clothing.

#### **7.2 Conditions for safe storage, including any incompatibilities**

Store in a cool, dry, ventilated area. Keep protected from direct sunlight and temperatures above 50°C.

#### **7.3 Specific end use (s)**

For heavy duty lubrication and such uses for indirect food contact equipment and machinery

## SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### 8.1 Control parameters

Workplace exposure limits:

Ingredients	LTEL 8 Hr	STEL 15 min	Note
Hydrocarbon aerosol propellant ( <0.1 butadiene)	1000 ppm	1250 ppm	EH40
Hydrocarbons,C7-C9 Isoalkanes <2% aromatics	800 mg/m <sup>3</sup>	–	EH40
Propan-2-ol	400 ppm	500 ppm	EH40

Biological limit value: Not established

PNECs, DNELs: Not established

### 8.2 Exposure controls

**8.2.1** Appropriate engineering controls: Ensure good ventilation /local exhaust ventilation to keep airborne contaminants below exposure limits.

**8.2.2** Personal protective equipment:



Eye / face protection: Safety goggles/glasses if there is a risk of eye contact.  
Skin protection: Nitrile gloves (EN 374). See glove manufacturer data for glove selection and breakthrough time for use conditions.  
Respiratory protection: Not required under normal circumstances.  
Thermal hazards: Not applicable

**8.2.3** Environmental exposure controls – See sections 6, 12, 13.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

Appearance/physical state: Aerosol  
Colour: White grease  
Odour: Mild, characteristic solvent  
Odour threshold: Not established  
pH: Not applicable  
Melting /freezing point: < 0<sup>0</sup>C  
IBP /boiling range: < 0<sup>0</sup>C  
Flash Point: <0<sup>0</sup> C  
Evaporation rate: Not established  
Flammability (gas): Extremely flammable  
Upper /lower explosive limits: 1.8% - 9.4% by vol  
Vapour pressure: Approx 3 bar at 20<sup>0</sup>C  
Vapour density: Not established  
Relative density: Not applicable  
Solubility: Negligible water miscibility  
Partition coefficient (n-octanol/water): Not established  
Auto-ignition temperature: Not established  
Decomposition temperature: Not established  
Viscosity: Not applicable  
Explosive properties: Not established  
Oxidising properties: None

## SECTION 10 STABILITY AND REACTIVITY

### 10.1 Reactivity

No dangerous reactions known under normal conditions of use.

### 10.2 Chemical Stability

Stable under proper storage and handling conditions.

### 10.3 Possibility of chemical reactions

No dangerous reactions known.

### 10.4 Conditions to avoid

Heat, flame and other ignition sources .Pressurised container: Protect from sunlight and do not Expose to temperatures exceeding 50<sup>0</sup>C. Do not pierce or burn even after use.

### 10.5 Incompatible materials

Avoid contact with strong oxidising agents

### 10.6 Hazardous decomposition products

None when used as directed.

## SECTION 11 TOXICOLOGICAL INFORMATION

### 11.1 Information on toxicological effects

Low order of acute toxicity.

#### 11.1.2. Mixtures

Acute toxicity	}	No data available
Irritation		
Corrosivity		
Sensitisation		
Repeated dose toxicity		
Carcinogenicity		
Mutagenicity		
Toxicity for reproduction		

#### Other information

May cause irritation and discomfort to eyes. Prolonged or repeated contact may cause skin irritation and dermatitis. High concentrations of vapours may cause drowsiness and dizziness. Ingestion may cause irritation to mouth and cause damage to respiratory system.

### Hydrocarbons,C7-C9 Isoalkanes <2% aromatics

Toxicity / Effect	Endpoint	Value	Organism	Method	Notes
Acute Tox -Oral	LD50	>5000mg/kg	Rat	OECD 401	Minimally toxic
Acute tox-Inhal	LC50	>21mg/l	Rat	OECD 403	Minimally toxic
Acute Tox- Derm	LD50	>2000mg/kg	Rabbit	OECD 402	Minimally toxic
Skin corrosion / Irritation				OECD 404	Moderately irritating to skin with prolonged exposure
Serious eye damage / Irritation				OECD 405	May cause mild discomfort to eyes
Sensitisation – Respiratory or Skin				OECD 406	Not expected to be respiratory or skin sensitiser.
Aspiration					May be fatal if swallowed and enters airways

Germ Cell Mutagenicity				OECD 471	Not expected to be germ cell mutagen.
Carcinogenicity					Not expected to cause cancer
Reproductive toxicity				OECD 414	Negative, analogous conclusion
Lactation					Not expected to cause harm to breast-fed children
Specific Target Organ Toxicity STOT-SE					May cause drowsiness or dizziness
STOT-repeated exposure				OECD 413	Not expected to cause organ damage from prolonged / repeated exposure

**Propan-2-ol**

Toxicity / Effect	Endpoint	Value	Organism	Method	Notes
Acute Tox -Oral	LD50	>2000mg/kg	Rat		
Acute Tox- Derm	LD50	>2000mg/kg	Rabbit		
Skin corrosion / Irritation			Rabbit		Not irritating
Serious eye damage / Irritation			Rabbit		Irritating
Sensitisation – Respiratory or Skin			Guinea pig	Buehler test	Not sensitising
Germ Cell Mutagenicity					No data available
Genotox in vitro				Ames test, Salmonella typhi – with/without	Not mutagenic

**Hydrocarbon aerosol propellant (<0.1% Butadiene)**

**General**

In low concentrations may cause narcotic effects. Symptoms include dizziness, headache, nausea and loss of co-ordination.

**SECTION 12 ECOLOGICAL INFORMATION:**

**Mixture**

- 12.1 Toxicity
- 12.2 Persistence and degradability
- 12.3 Bioaccumulative potential
- 12.4 Mobility in soil
- 12.4 results of PBT and vPvB assessment
- 12.6 Other adverse effects.

Harmful to aquatic life with long lasting effects

No data available

**Hydrocarbons,C7-C9 Isoalkanes <2% aromatics**

**12.1 Toxicity** – Expected to be toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

Test	Duration	Organism	Method	Result	Notes
Aquatic -acute	48 hrs	Daphnia magna	EL50	2.4mg/l	Analagous material

Aquatic -acute	72 hrs	Pseudokirchneriella subcapitata	NOELR	6.3mg/l	Analagous material
Aquatic -acute	72 hrs	Pseudokirchneriella subcapitata	EL50	29mg/l	Analagous material
Aquatic -acute	96 hrs	Oncorhynchus mykiss	LL50	18.4mg/l	Analagous material
Aquatic -chronic	21 days	Daphnia magna	NOEC	0.17mg/l	Analagous material
Aquatic -chronic	21 days	Daphnia magna	LOEC	0.32mg/l	Analagous material

**12.2 Persistence and degradability** – Expected to be inherently biodegradable. Transformation due to hydrolysis and photolysis not expected to be significant. Expected to rapidly degrade in air

Media	Test type	Duration	Result
Water	Ready biodegradability	28 days	22% degraded

**12.3 Bioaccumulative potential** – Not determined.

**12.4 Mobility in soil** – Highly volatile, will rapidly partition to air. Not expected to partition to sediment and wastewater solids..

**12.5 Results of PBT and vPvB assessment** – Contains no PBT or vPvB components

**12.6 Other adverse effects** – Material is classified as a VOC.

## SECTION 13 DISPOSAL CONSIDERATIONS:

### 13.1 Waste Treatment Methods

Dispose in a regulated landfill site or other method for hazardous or toxic waste. Dispose of in accordance with local and national regulations.

## SECTION 14. TRANSPORT INFORMATION:

<b>14.1 UN number</b>	1950
<b>14.2 UN proper shipping name</b>	Aerosols
<b>14.3 Transport hazard class</b>	2 (UN / IMDG)
<b>ADR Classification code</b>	5F
<b>14.4 Packing group</b>	None
<b>14.5 Environmental hazards</b>	Not applicable

## SECTION 15. REGULATORY INFORMATION:

### 15.1 Safety, health and environmental regulations/legislation specific for the mixture

REACH - 1907/2006  
 CLP - 1272/2008  
 DPD - 199/45/EC  
 COSHH - 2002 (as amended)

### 15.2 Chemical safety assessment

A CSA has not been carried out for this mixture.

## SECTION 16. OTHER INFORMATION:

### Legend

LTEL	Long term exposure limit
STEL (SE)	Short term exposure limit (Single exposure)
STOT	Specific target organ toxicity
PNEC	Predicted no effect concentration
DNEL	Derived no effect level

**Classification methods used to derive classification of mixture**

Classification according to calculation procedure detailed in EC1272/2008

**Additional information****Hazard statements –referred to in sect 3**

H220	Extremely flammable gas
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H411	Toxic to aquatic life with long-lasting effects

This safety data sheet has been produced based on information supplied by the manufacturers of the materials therein and is believed to be accurate. No warranty is expressed or implied by this information. It is for the user to satisfy themselves of the suitability of the product for their own purposes.