



MULTI PURPOSE WHITE SPRAY GREASE WHITE MAINTENANCE GREASE

Product Overview

New Tech Lubes White Maintenance Grease is a, high performance, Calcium soap based grease developed to withstand high surface loads.

Typical Applications

- **Home**
- **Industrial**
- **Marine**
- **Automotive**
- **Garden & Leisure Equipment**

Features and Benefits

- Provide lubrication for all moving parts including- locks, hinges, pivots, chains, bearings, cables & slides.
- Prevents corrosion and attack from water
- Apply evenly as a fluid and set as a fully formed grease
- Be clean in use, white grease, with white EP Additives to prevent black staining and unnecessary mess.
- Suitable for marine applications.
- Also available in bulk

Directions for Storage and Use

Product is to be stored in a clean, dry, storage area in its original sealed packaging.

*Shelf Life (unopened) – 3 years approx **

Do not mix with other lubricants if compatibility is not known, for best results purge system of other lubricants. Apply to clean, dry parts only.

Caution: Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not puncture or incinerate even when empty. Do not spray on any naked flame or any incandescent material

Disclaimer

The data sheet is based on personal knowledge and experience and is given as a guideline to its possible uses. It does not take into account variables or conditions out of our control that can affect our product in any way. It is the users' sole responsibility to ensure that the product is suitable for the purpose for which it is being used and this data does not in any way form a warranty. If you are unsure of its suitability please contact us and we will be happy to discuss your needs and supply a sample for testing if required. New Tech Lubes Ltd is committed to supplying the best products and may therefore change the information in this specification at any time.

| Available Sizes |
|-----------------|
| 500ml Aerosol |
| |
| |
| |
| |
| |
| |
| |

| Available Grades |
|------------------|
| |
| |

| Physical Characteristics | |
|--------------------------|----------------|
| Base | Calcium Soap |
| ASTM penetration | 275/295 |
| Melting Point | 180°C |
| Rust Protection | Emcor Pass |
| Operating temperature | -20°C - +140°C |
| Bearing Rig Test | R2FA Pass |
| Weld Load | 550kg |
| Scar Diameter | 0.35 mm |

Safety Data Sheets

Safety data sheets are available for download from our website, scan the QR code for a direct link to the file.



www.newtechlubes.com